



IDRIS

MPI

Dimitri Lecas - Rémi Lacroix - Serge Van Criekingen - Myriam Peyrounette

CNRS — IDRIS

v5.3 March 13th 2025



Plan I

Introduction

- Availability and updating
- Introduction
- Concept of message passing
- Distributed memory
- History
- Library

Environment

Point-to-point Communications

- General Concepts
- Blocking send and receive
- Predefined MPI Datatypes
- Other Possibilities

Collective communications

- General concepts
- Global synchronization : `MPI_Barrier()`
- Global distribution : `MPI_Bcast()`
- Selective distribution : `MPI_Scatter()`
- Collection : `MPI_Gather()`
- Gather-to-all : `MPI_Allgather()`
- Extended gather : `MPI_Gatherv()`

Plan II

- Collection and distribution : MPI_Alltoall()
- Global reduction
- Additions

Communication Modes

- Point-to-Point Send Modes

- Blocking call

- Synchronous Sends

- Buffered sends

- Standard sends

- Number of received elements

- Nonblocking communication

- One-Sided Communications

Derived datatypes

- Introduction

- Contiguous datatypes

- Constant stride

- Commit derived datatypes

- Examples

- The datatype "matrix row"

- The datatype "matrix line"

- The datatype "matrix block"

- Homogenous datatypes of variable strides

Plan III

- Size of MPI datatype
- Heterogenous datatypes
- Conclusion
- Memento

Communicators

- Introduction
- Example
- Default communicator
- Groups and communicators
- Partitioning of a communicator
- Topologies
 - Cartesian topologies
 - Subdividing a Cartesian topology

MPI-IO

- Introduction
- File Manipulation
- Data access : Concepts
- Noncollective data access
 - Data access with explicit offsets
 - Data access with individual file pointers
 - Data access with shared file pointers
- Collective data access

Plan IV

- Data access with explicit offsets
- Data access with individual file pointers
- Data access with shared file pointers

Positioning the file pointers

Nonblocking Data Access

- Data Access with Explicit Offsets
- Data access with individual file pointers
- Nonblocking and collective data access routines

MPI 4.x

MPI-IO Views

- Definition
- Subarray datatype constructor
- Reading non-overlapping sequences of data segments in parallel
- Reading data using successive views
- Dealing with holes in datatypes

Conclusion

Introduction

Introduction

Availability and updating

This document is likely to be updated regularly. The most recent version is available on the Web server of IDRIS : <http://www.idris.fr/formations/mpl/>

- IDRIS
Institut for Development and Resources in Intensive Scientific Computing
Rue John Von Neumann
Bâtiment 506
BP 167
91403 ORSAY CEDEX
France
<http://www.idris.fr>
- Translated with the help of Cynthia TAUPIN.

Parallelism

The goal of parallel programming is to :

- Reduce elapsed time.
- Do larger computations.
- Exploit parallelism of modern processor architectures (multicore, multithreading).

For group work, coordination is required. [MPI](#) is a library which allows process coordination by using a message-passing paradigm.

Introduction

Sequential programming model

- The program is executed by one and only one process.
- All the variables and constants of the program are allocated in the memory of the process.
- A process is executed on a physical processor of the machine.




Figure 1 – Sequential programming model

Introduction

Message passing programming model

- The program is written in a classic language (Fortran, C, C++, etc.).
- All the program variables are private and reside in the local memory of each process.
- Each process has the possibility of executing different parts of a program.
- A variable is exchanged between two or several processes via a programmed call to specific subroutines.




Figure 2 – Message Passing Programming Model

Introduction

Message Passing concepts

If a message is sent to a process, the process must receive it.




Figure 3 – Message Passing

Introduction

Message content

- A message consists of data chunks passing from the sending process to the receiving process/pocesses.
- In addition to the data (scalar variables, arrays, etc.) to be sent, a message must contain the following information :
 - The identifier of the sending process
 - The datatype
 - The length
 - The identifier of the receiving process




Figure 4 – Message Construction

Introduction

Environment

- The exchanged messages are interpreted and managed by an environment comparable to telephony, e-mail, postal mail, etc.
- The message is sent to a specified address.
- The receiving process must be able to classify and interpret the messages which are sent to it.
- The environment in question is MPI ([Message Passing Interface](#)). An MPI application is a group of autonomous processes, each executing its own code and communicating via calls to MPI library subroutines.

Introduction

Supercomputer architecture

Most supercomputers are distributed-memory computers. They are made up of many nodes and memory is shared within each node.




Figure 5 – Supercomputer architecture

Introduction

Jean Zay

- 1 116 nodes
- 2 Intel Cascade Lake processor (20 cores), 2,5 Ghz by node
- 4 GPU Nvidia V100 by node (on 391 nodes)
- 44 640 cores
- 214 TB (192 GB by node)



Introduction

MPI vs OpenMP

OpenMP uses a shared memory paradigm, while MPI uses a distributed memory paradigm.




Figure 6 – MPI scheme




Figure 7 – OpenMP scheme

Introduction

Domain decomposition

A schema that we often see with MPI is domain decomposition. Each process controls a part of the global domain and mainly communicates with its neighbouring processes.




Figure 8 – Decomposition in subdomains

Introduction

History

- **Version 1.0** : June 1994, the MPI (Message Passing Interface) Forum, with the participation of about forty organisations, developed the definition of a set of subroutines concerning the MPI library.
- **Version 1.1** : June 1995, only minor changes.
- **Version 1.2** : 1997, minor changes for more consistency in the names of some subroutines.
- **Version 1.3** : September 2008, with clarifications of the MPI 1.2 version which are consistent with clarifications made by MPI-2.1.
- **Version 2.0** : Released in July 1997, important additions which were intentionally not included in MPI 1.0 (process dynamic management, one-sided communications, parallel I/O, etc.).
- **Version 2.1** : June 2008, with clarifications of the MPI 2.0 version but without any changes.
- **Version 2.2** : September 2009, with only "small" additions.
- **Version 3.0** : September 2012, add nonblocking collective communications, new fortran bindings, etc.
- **Version 3.1** : June 2015 with clarifications and small additions.

Introduction

MPI 4.0

Version 4.0 : June 2021

- Large count
- Partitioned communication
- MPI Session

Version 4.1 : November 2023

Introduction

Library

- Website of MPI Forum <http://www.mpi-forum.org>
- Standard available in PDF on <http://www.mpi-forum.org/docs/>
- William Gropp, Ewing Lusk, and Anthony Skjellum. *Using MPI, third edition Portable Parallel Programming with the Message-Passing Interface*, MIT Press, 2014.
- William Gropp, Torsten Hoefler, Rajeev Thakur and Erwing Lusk : *Using Advanced MPI Modern Features of the Message-Passing Interface*, MIT Press, 2014.
- Victor Eijkhout : The Art of HPC <http://theartofhpc.com>

Introduction

Open source MPI implementations

These can be installed on a large number of architectures but their performance results are generally inferior to the implementations of the constructors.

- MPICH : <http://www.mpich.org>
- Open MPI : <http://www.open-mpi.org>

Introduction

Tools

- Debuggers
 - Totalview
<https://totalview.io>
 - DDT
<https://www.linaroforge.com/linaro-ddt>
- Performance measurement
 - FPMPI : *FPMPI*
<http://www.mcs.anl.gov/research/projects/fpm MPI/WWW/>
 - Scalasca : *Scalable Performance Analysis of Large-Scale Applications*
<http://www.scalasca.org>
 - MUST : *MPI Runtime Correctness Analysis*
<https://itc.rwth-aachen.de/must/>

Introduction

Open source parallel scientific libraries

- **ScaLAPACK** : Linear algebra problem solvers using direct methods.
<http://www.netlib.org/scalapack/>
- **PETSc** : Linear and non-linear algebra problem solvers using iterative methods.
<https://petsc.org/release/>
- **PaStiX** : Parallel sparse direct Solvers.
<https://solverstack.gitlabpages.inria.fr/pastix/>
- **FFTW** : Fast Fourier Transform.
<http://www.fftw.org>
- **HDF5** : Read and write on files.
<https://www.hdfgroup.org/solutions/hdf5/>

Environment

Environment

Description

- Every program unit calling MPI subroutines has to include a header file. In Fortran, we use the `mpi_f08` module introduced in MPI-3. Before in MPI-2, we used the *module mpi*, and in MPI-1, it was the `mpif.h` file).
- The `MPI_Init()` subroutine initializes the MPI environment :

```
MPI_INIT(code)  
integer, optional, intent(out) :: code
```

- The `MPI_Finalize()` subroutine disables this environment :

```
MPI_FINALIZE(code)  
integer, optional, intent(out) :: code
```

Differences between C/C++ and Fortran

In a C/C++ program :

- you need to include the header file `mpi.h`;
- the `code` argument is the return value of MPI subroutines ;
- except for `MPI_Init()` , the function arguments are identical to Fortran ;
- the syntax of the subroutines changes : only the MPI prefix and the first following letter are in upper-case letters.

```
int MPI_Init(int *argc, char ***argv);
int MPI_Finalize(void);
```

Environment

Communicators

- All the MPI operations occur in a defined set of processes, called **communicator**.
The default communicator is `MPI_COMM_WORLD`, which includes all the active processes.




Figure 9 – MPI_COMM_WORLD Communicator

Environment

Termination of a program

Sometimes, a program encounters some issue during its execution and has to stop prematurely. For example, we want the execution to stop if one of the processes cannot allocate the memory needed for its calculation. In this case, we call the `MPI_Abort()` subroutine instead of the Fortran instruction `stop` (Or `exit` in C).

```
MPI_ABORT(comm, erreur, code)

TYPE(MPI_Comm), intent(in)      :: comm
integer, intent(in)              :: error
integer, optional, intent(out)   :: code
```

- `comm` : the communicator of which all the processes will be stopped ; it is advised to use `MPI_COMM_WORLD` in general ;
- `error` : the error number returned to the UNIX environment.

Code

It is not necessary to check the `code` value (return value in C) after calling MPI routines. By default, when MPI encounters a problem, the program is automatically stopped as in an implicit call to `MPI_Abort()` subroutine.

Environment

Rank and size

- At any moment, we have access to the number of processes managed by a given communicator by calling the `MPI_Comm_size()` subroutine :

```
MPI_COMM_SIZE(comm, nb_procs, code)

TYPE(MPI_Comm) :: comm
integer, intent(out) :: nb_procs
integer, optional, intent(out) :: code
```

- Similarly, the `MPI_Comm_rank()` subroutine allows us to obtain the rank of an active process (i.e. its instance number, between 0 and `MPI_Comm_size() - 1`) :

```
MPI_COMM_RANK(comm, rank, code)

TYPE(MPI_Comm), intent(in) :: comm
integer, intent(out) :: rank
integer, optional, intent(out) :: code
```

Environment

Example

```
1 program who_am_I
2 use mpi_f08
3 implicit none
4 integer :: nb_procs,rank
5
6 call MPI_INIT()
7
8 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
9 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
10
11 print *,'I am the process ',rank,' among ',nb_procs
12
13 call MPI_FINALIZE()
14 end program who_am_I
```

```
> mpieexec -n 7 who_am_I
I am process 3 among 7
I am process 0 among 7
I am process 4 among 7
I am process 1 among 7
I am process 5 among 7
I am process 2 among 7
I am process 6 among 7
```

Compilation and execution of an MPI code

- To **compile** an MPI code, we use a compiler *wrapper*, which makes the link with the chosen MPI library.
- This *wrapper* is different depending on the programming language, the compiler and the MPI library. For example : `mpif90`, `mpifort`, `mpicc`, ...

```
> mpif90 <options> -c source.f90  
> mpif90 source.o -o my_executable_file
```

- To **execute** an MPI code, we use an MPI launcher, which runs the execution on a given number of processes.
- The `mpiexec` launcher is defined by the MPI standard. There are also non-standard launchers, such as `mpirun`.

```
> mpiexec -n <number of processes> my_executable_file
```

MPI Hands-On – Exercise 1 : MPI Environment

- Write an MPI program in such a way that each process prints a message, which indicates whether its rank is **odd** or **even**. For example :

```
> mpiexec -n 4 ./even_odd  
I am process 0, my rank is even  
I am process 2, my rank is even  
I am process 3, my rank is odd  
I am process 1, my rank is odd
```

- To test whether the rank is odd or even, the Fortran intrinsic function corresponding to the *modulo* operation is **mod** :

```
mod(a,b)
```

(use **%** symbol in C : $a \% b$)

- To compile your program, use the command **make**
- To execute your program, use the command **make exe**
- For the program to be recognized by the Makefile, it must be named **even_odd.f90** (or **even_odd.c**)

Point-to-point Communications

Point-to-point Communications

General Concepts

A **point-to-point** communication occurs between two processes : the **sender** process and the **receiver** process.




Figure 10 – Point-to-point communication

Point-to-point Communications

General Concepts

- The sender and the receiver are identified by their **ranks** in the communicator.
- The object communicated from one process to another is called **message**.
- A message is defined by its **envelope**, which is composed of :
 - the rank of the sender process
 - the rank of the receiver process
 - the message tag
 - the communicator in which the transfer occurs
- The exchanged data has a **datatype** (integer, real, etc, or individual derived datatypes).
- There are several transfer **modes**, which use different protocols.
- If two messages are sent with the same envelope, the order of receipt and sending are the same.

Point-to-point Communications

Blocking Send `MPI_Send`

```
MPI_SEND(buf, count, datatype, dest, tag, comm, code)

TYPE(*), dimension(..), intent(in) :: buf
integer, intent(in) :: count, dest, tag
TYPE(MPI_Datatype), intent(in) :: datatype
TYPE(MPI_Comm), intent(in) :: comm
integer, optional, intent(out) :: code
```

Sending, from the address `buf`, a message of `count` elements of type `datatype`, tagged `tag`, to the process of rank `dest` in the communicator `comm`.

Remark :

This call is blocking : the execution remains blocked until the message can be re-written without risk of overwriting the value to be sent. In other words, the execution is blocked as long as the message has not been received.

Point-to-point Communications

Blocking Receive `MPI_Recv`

```
MPI_RECV(buf, count, datatype, source, tag, comm, status_msg, code)

TYPE(*), dimension(..), intent(in) :: buff
integer, intent(in)           :: count, source, tag
TYPE(MPI_Datatype), intent(in) :: datatype
TYPE(MPI_Comm), intent(in)   :: comm
TYPE(MPI_Status)              :: status_msg
integer, optional, intent(out) :: code
```

Receiving, at the address `buf`, a message of `count` elements of type `datatype`, tagged `tag`, from the process of rank `source` in the communicator `comm`.

Remarks :

- `status_msg` stores the state of a receive operation : source, tag, code,
- An `MPI_Recv` can only be associated to an `MPI_Send` if these two calls have the same envelope (`source, dest, tag, comm`).
- This call is blocking : the execution remains blocked until the message content corresponds to the received message.

Point-to-point Communications

Example (see Fig. 10)

```
1 program point_to_point
2   use mpi_f08
3   implicit none
4
5   TYPE(MPI_Status) :: status_msg
6   integer, parameter :: tag=100
7   integer :: rank,value
8
9   call MPI_INIT()
10
11  call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
12
13  if (rank == 2) then
14    value=1000
15    call MPI_SEND(value,1,MPI_INTEGER,5,tag,MPI_COMM_WORLD)
16  elseif (rank == 5) then
17    call MPI_RECV(value,1,MPI_INTEGER,2,tag,MPI_COMM_WORLD,status_msg)
18    print *, 'I, process 5, I received ',value,' from the process 2.'
19  end if
20
21  call MPI_FINALIZE()
22
23 end program point_to_point
```

```
> mpieexec -n 7 point_to_point
I, process 5, I received 1000 from the process 2
```

Point-to-point Communications

Fortran MPI Datatypes

MPI Type	Fortran Type
<code>MPI_INTEGER</code>	INTEGER
<code>MPI_REAL</code>	REAL
<code>MPI_DOUBLE_PRECISION</code>	DOUBLE PRECISION
<code>MPI_COMPLEX</code>	COMPLEX
<code>MPI_LOGICAL</code>	LOGICAL
<code>MPI_CHARACTER</code>	CHARACTER
<code>MPI_BYTE</code>	

Point-to-point Communications

Fortran MPI Datatype

- The Fortran 95 language introduces two intrinsic functions `selected_int_kind()` and `selected_real_kind()` which make it possible to define `precision` and/or the `range` of an integer, real or complex number.
- MPI provides portability of these data types with

`MPI_TYPE_CREATE_F90_INTEGER()`, `MPI_TYPE_CREATE_F90_REAL()` and
`MPI_TYPE_CREATE_F90_COMPLEX()`

```
MPI_TYPE_CREATE_F90_INTEGER(r, newtype, code)

INTEGER, INTENT(IN) :: r
TYPE(MPI_Datatype), INTENT(OUT) :: newtype
INTEGER, OPTIONAL, INTENT(OUT) :: code

MPI_TYPE_CREATE_F90_REAL(p, r, newtype, code)

INTEGER, INTENT(IN) :: p, r
TYPE(MPI_Datatype), INTENT(OUT) :: newtype
INTEGER, OPTIONAL, INTENT(OUT) :: code
```

```
! Kind for double precision
integer, parameter :: dp = selected_real_kind(15, 307)
! Kind for long int
integer, parameter :: li = selected_int_kind(15)
integer(kind=li) :: nbloc
real(kind=dp) :: width
call MPI_TYPE_CREATE_F90_INTEGER(15, typeli)
call MPI_TYPE_CREATE_F90_REAL(15, 307, typedp)
```

Point-to-point Communications

Other possibilities

- When receiving a message, the rank of the sender process and the tag can be replaced by « *jokers* » : `MPI_ANY_SOURCE` and `MPI_ANY_TAG`, respectively.
- A communication involving the dummy process of rank `MPI_PROC_NULL` has no effect.
- `MPI_STATUS_IGNORE` is a predefined constant, which can be used instead of the status variable.
- It is possible to send more complex data structures by creating [derived datatypes](#).
- There are other operations, which carry out both send and receive operations simultaneously : `MPI_Sendrecv()` and `MPI_Sendrecv_replace()`.

Point-to-point Communications

Simultaneous send and receive MPI_Sendrecv

```
MPI_SENDRIVE(sendbuf, sendcount, sendtype,
              dest, sendtag,
              recvbuf, recvcount, recvtype,
              source, recvtag, comm, status_msg, code)

TYPE(*), dimension(..), intent(in) :: sendbuf
TYPE(*), dimension(..)           :: recvbuf
integer, intent(in)             :: sendcount, recvcount
integer, intent(in)             :: source, dest, sendtag, recvtag
TYPE(MPI_Datatype), intent(in)  :: sendtype, recvtype
TYPE(MPI_Comm), intent(in)      :: comm
TYPE(MPI_Status)                :: status_msg
integer, optional, intent(out)   :: code
```

- Sending, from the address `sendbuf`, a message of `sendcount` elements of type `sendtype`, tagged `sendtag`, to the process `dest` in the communicator `comm`;
- Receiving, at the address `recvbuf`, a message of `recvcount` elements of type `recvtype`, tagged `recvtag`, from the process `source` in the communicator `comm`.

Remark :

- Here, the receiving zone `recvbuf` must be different from the sending zone `sendbuf`.

Point-to-point Communications

Simultaneous send and receive `MPI_Sendrecv`




Figure 11 – `sendrecv` Communication between the Processes 0 and 1

Point-to-point Communications

Example (see Fig. 11)

```
1 program sendrecv
2 use mpi_f08
3 implicit none
4 integer :: rank,value,num_proc
5 integer,parameter :: tag=110
6
7 call MPI_INIT()
8 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
9
10 ! We define the process we'll communicate with (we suppose that we have exactly 2 processes)
11 num_proc=mod(rank+1,2)
12
13 call MPI_RECV(rank+1000,1,MPI_INTEGER,num_proc,tag,value,1,MPI_INTEGER, &
14 num_proc,tag,MPI_COMM_WORLD,MPI_STATUS_IGNORE)
15
16 print *,'I, process ',rank,', I received',value,'from process ',num_proc
17
18 call MPI_FINALIZE()
19 end program sendrecv
```

```
> mpieexec -n 2 sendrecv
I, process 1, I received 1000 from process 0
I, process 0, I received 1001 from process 1
```

Point-to-point Communications

Be careful !

In the case of a **synchronous** implementation of the `MPI_Send()` subroutine, if we replace the `MPI_Sendrecv()` subroutine in the example above by `MPI_Send()` followed by `MPI_Recv()`, the code will deadlock. Indeed, each of the two processes will wait for a receipt confirmation, which will never come because the two sending operations would stay suspended.

```
call MPI_SEND(rank+1000,1,MPI_INTEGER,num_proc,tag,MPI_COMM_WORLD)
call MPI_RECV(value,1,MPI_INTEGER,num_proc,tag,MPI_COMM_WORLD,status_msg)
```

Point-to-point Communications

Simultaneous send and receive `MPI_Sendrecv_replace`

```
MPI_SENDREREV_REPLACE(buf, count, datatype,
                      dest, sendtag,
                      source, recvtag, comm, status_msg, code)

TYPE(*), dimension(..)      :: buf
integer, intent(in)        :: count, source, dest, sendtag, recvtag
TYPE(MPI_Datatype), intent(in) :: datatype
TYPE(MPI_Comm), intent(in)  :: comm
TYPE(MPI_Status)            :: status_msg
integer, optional, intent(out) :: code
```

- Sending, from the address `buf`, a message of `count` elements of type `datatype`, tagged `sendtag`, to the process `dest` in the communicator `comm` ;
- Receiving a message at the same address, with same count elements and same datatype, tagged `recvtag`, from the process `source` in the communicator `comm`.

Remark :

- Contrary to the usage of `MPI_Sendrecv`, the receiving zone is the same here as the sending zone `buf`.

Point-to-point Communications

Example

```
1 program wildcard
2 use mpi_f08
3 implicit none
4 integer, parameter :: m=4,tag=11
5 integer, dimension(m,m) :: A
6 integer :: nb_procs,rank,i
7 TYPE(MPI_Status) :: status_msg
8
9 call MPI_INIT()
10 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
11 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
12 A(:,:) = 0
13
14 if (rank == 0) then
15 ! Initialisation of the matrix A on the process 0
16 A(:,:) = reshape((/ (i,i=1,m*m) /), (/ m,m /))
17 ! Sending of 3 elements of the matrix A to the process 1
18 call MPI_SEND(A(1,1),3,MPI_INTEGER,1,tag1,MPI_COMM_WORLD)
19 else
20 ! We receive the message
21 call MPI_RECV (A(1,2),3, MPI_INTEGER ,MPI_ANY_SOURCE,MPI_ANY_TAG, &
22 MPI_COMM_WORLD,status_msg)
23 print *, 'I, process ',rank,', I received 3 elements from the process ', &
24 status_msg(MPI_SOURCE), 'with tag', status_msg( MPI_TAG ), &
25 " the elements are ", A(1:3,2)
26 end if
27 call MPI_FINALIZE()
28 end program wildcard
```

Point-to-point Communications

```
> mpiexec -n 2 wildcard
I, process      1, I received 3 elements from the process      0
with tag      11 the elements are      1      2      3
```

MPI Hands-On – Exercise 2 : Ping-pong

- Point to point communications : *Ping-Pong* between two processes
- This exercise is composed of 3 steps :
 1. *Ping* : complete the script `ping_pong_1.f90` in such a way that the process 0 sends a message containing 1000 random reals to process 1.
 2. *Ping-Pong* : complete the script `ping_pong_2.f90` in such a way that the process 1 sends back the message to the process 0, and measure the communication duration with the `MPI_Wtime()` function.
 3. *Ping-Pong match* : complete the script `ping_pong_3.f90` in such a way that processes 0 and 1 perform 9 *Ping-Pong*, while varying the message size, and measure the communication duration each time. The corresponding bandwidths will be printed.

MPI Hands-On – Exercise 2 : Ping-pong

Remarks :

- To compil the first step : `make ping_pong_1`
- To execute the first step : `make exe1`
- To compil the second step : `make ping_pong_2`
- To execute the second step : `make exe2`
- To compil the last step : `make ping_pong_3`
- To execute the last step : `make exe3`
- The generation of random numbers uniformly distributed in the range [0,1[is made by calling the Fortran `random_number` subroutine :

```
call random_number(variable)
```

`variable` can be a scalar or an array

- The time duration measurements can be done like this :

```
time_begin=MPI_WTIME()  
.....  
time_end=MPI_WTIME()  
print ("(... in",f8.6," secondes.)'),time_end-time_begin
```

Collective communications

Collective communications

General concepts

- Collective communications allow making a series of point-to-point communications in one single call.
- A collective communication always concerns all the processes of the indicated communicator.
- For each process, the call ends when its participation in the collective call is completed, in the sense of point-to-point communications (therefore, when the concerned memory area can be changed).
- The management of tags in these communications is transparent and system-dependent. Therefore, they are never explicitly defined during calls to subroutines. An advantage of this is that collective communications never interfere with point-to-point communications.

Collective communications

Types of collective communications

There are three types of subroutines :

1. One which ensures global synchronizations : `MPI_Barrier()`
2. Ones which only transfer data :
 - Global distribution of data : `MPI_Bcast()`
 - Selective distribution of data : `MPI_Scatter()`
 - Collection of distributed data : `MPI_Gather()`
 - Collection of distributed data by all the processes : `MPI_Allgather()`
 - Collection and selective distribution by all the processes of distributed data :
`MPI_Alltoall()`
3. Ones which, in addition to the communications management, carry out operations on the transferred data :
 - Reduction operations (sum, product, maximum, minimum, etc.), whether of a predefined or personal type : `MPI_Reduce()`
 - Reduction operations with distributing of the result (this is in fact equivalent to an `MPI_Reduce()` followed by an `MPI_Bcast()`) : `MPI_Allreduce()`

Collective communications

Global synchronization : MPI_Barrier()




Figure 12 – Global Synchronization : MPI_Barrier ()

```
MPI_BARRIER(comm,code)  
  
TYPE(MPI_Comm),intent(in)      :: comm  
integer, optional, intent(out) :: code
```

Collective communications

Global distribution : `MPI_Bcast()`




Figure 13 – Global distribution : `MPI_Bcast()`

Collective communications

Global distribution : `MPI_Bcast()`

```
MPI_BCAST(buffer, count, datatype, root, comm, code)

TYPE(*), dimension(..)      :: buffer
integer, intent(in)         :: count, root
TYPE(MPI_Datatype), intent(in) :: datatype
TYPE(MPI_Comm), intent(in)   :: comm
integer, optional, intent(out) :: code
```

1. Send, starting at position `buffer`, a message of `count` element of type `datatype`, by the `root` process, to all the members of communicator `comm`.
2. Receive this message at position `buffer` for all the processes other than the `root`.

Collective communications

Example of MPI_Bcast()

```
1 program bcast
2 use mpi_f08
3 implicit none
4
5 integer :: rank,value
6
7 call MPI_INIT()
8 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
9
10 if (rank == 2) value=rank+1000
11
12 call MPI_BCAST(value,1,MPI_INTEGER,2,MPI_COMM_WORLD)
13
14 print *, 'I, process ',rank,', received ',value,' of process 2'
15
16 call MPI_FINALIZE()
17
18 end program bcast
```

```
> mpieexec -n 4 bcast
I, process 2, received 1002 of process 2
I, process 0, received 1002 of process 2
I, process 1, received 1002 of process 2
I, process 3, received 1002 of process 2
```

Collective communications

Selective distribution : `MPI_Scatter()`




Figure 14 – Selective distribution : MPI_Scatter ()

Collective communications

Selective distribution : MPI_Scatter()

```
MPI_SCATTER(sendbuf, sendcount, sendtype,
            recvbuf, recvcount, recvtype, root, comm, code)

TYPE(*), dimension(..)      :: sendbuf, recvbuf
integer, intent(in)         :: sendcount, recvcount, root
TYPE(MPI_Datatype), intent(in) :: sendtype, recvtype
TYPE(MPI_Comm), intent(in)   :: comm
integer, optional, intent(out) :: code
```

1. Scatter by process `root`, starting at position `sendbuf`, message `sendcount` element of type `sendtype`, to all the processes of communicator `comm`.
2. Receive this message at position `recvbuf`, of `recvcount` element of type `recvtype` for all processes of communicator `comm`.

Remarks :

- The couples (`sendcount`, `sendtype`) and (`recvcount`, `recvtype`) must represent the same quantity of data.
- Data are scattered in chunks of same size ; a chunk consists of `sendcount` elements of type `sendtype`.
- The i-th chunk is sent to the i-th process.

Collective communications

Example of MPI_Scatter()

```
1 program scatter
2 use mpi_f08
3 implicit none
4 integer, parameter :: nb_values=8
5 integer :: nb_procs,rank,block_length,i,code
6 real, allocatable, dimension(:) :: values,recvdata
7
8 call MPI_INIT()
9 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
10 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
11 block_length=nb_values/nb_procs
12 allocate(recvdata(block_length))
13 if (rank == 2) then
14     allocate(values(nb_values))
15     values(:)=//(1000.+i,i=1,nb_values)/
16     print *, 'I, process ',rank,' send my values array : ',&
17             values(1:nb_values)
18 end if
19 call MPI_SCATTER(values,block_length,MPI_REAL,recvdata,block_length, &
20                  MPI_REAL,Z,MPI_COMM_WORLD)
21 print *, 'I, process ',rank,', received ', recvdata(1:block_length), &
22          ' of process 2'
23 call MPI_FINALIZE()
24
25 end program scatter
```

```
> mpieexec -n 4 scatter
I, process 2 send my values array :
1001. 1002. 1003. 1004. 1005. 1006. 1007. 1008.

I, process 0, received 1001. 1002. of processus 2
I, process 1, received 1003. 1004. of processus 2
I, process 3, received 1007. 1008. of processus 2
I, process 2, received 1005. 1006. of processus 2
```

Collective communications

Collection : MPI_Gather ()




Figure 15 – Collection : MPI_Gather ()

Collective communications

Collection : MPI_Gather()

```
MPI_GATHER(sendbuf, sendcount, sendtype,
            recvbuf, recvcount, recvtype, root, comm, code)

TYPE(*), dimension(..), intent(in) :: sendbuf
TYPE(*), dimension(..)           :: recvbuf
integer, intent(in)              :: sendcount, recvcount, root
TYPE(MPI_Datatype), intent(in)   :: sendtype, recvtype
TYPE(MPI_Comm), intent(in)       :: comm
integer, optional, intent(out)   :: code
```

1. Send for each process of communicator `comm`, a message starting at position `sendbuf`, of `sendcount` element type `sendtype`.
2. Collect all these messages by the `root` process at position `recvbuf`, `recvcount` element of type `recvtype`.

Remarks :

- The couples (`sendcount`, `sendtype`) and (`recvcount`, `recvtype`) must represent the same size of data.
- The data are collected in the order of the process ranks.

Collective communications

Collection : MPI_Gather()

```
1 program gather
2 use mpi_f08
3 implicit none
4 integer, parameter :: nb_values=8
5 integer :: nb_procs,rank,block_length,i
6 real, dimension(nb_values) :: recvdata
7 real, allocatable, dimension(:) :: values
8
9 call MPI_INIT()
10 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
11 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
12
13 block_length=nb_values/nb_procs
14
15 allocate(values(block_length))
16
17 values(:)=/(1000.+rank*block_length+i,i=1,block_length)/
18 print *,'I, process ',rank,' sent my values array : ',&
19 values(1:block_length)
20
21 call MPI_GATHER(values,block_length,MPI_REAL,recvdata,block_length, &
22 MPI_REAL,2,MPI_COMM_WORLD)
23
24 if (rank == 2) print *,'I, process 2', ' received ',recvdata(1:nb_values)
25
26 call MPI_FINALIZE()
27
28 end program gather
```

```
> mpixexec -n 4 gather
I, process 1 sent my values array :1003. 1004.
I, process 0 sent my values array :1001. 1002.
I, process 2 sent my values array :1005. 1006.
I, process 3 sent my values array :1007. 1008.

I, process 2, received 1001. 1002. 1003. 1004. 1005. 1006. 1007. 1008.
```

Collective communications

Gather-to-all : `MPI_Allgather()`




Figure 16 – Gather-to-all : `MPI_Allgather()`

Collective communications

Gather-to-all : MPI_Allgather()

Corresponds to an MPI_Gather() followed by an MPI_Bcast() :

```
MPI_ALLGATHER(sendbuf, sendcount, sendtype,
               recvbuf, recvcount, recvtype, comm, code)

TYPE(*), dimension(..), intent(in) :: sendbuf
TYPE(*), dimension(..)           :: recvbuf
integer, intent(in)              :: sendcount, recvcount
TYPE(MPI_Datatype), intent(in)   :: sendtype, recvtype
TYPE(MPI_Comm), intent(in)       :: comm
integer, optional, intent(out)   :: code
```

1. Send by each process of communicator `comm`, a message starting at position `sendbuf`, of `sendcount` element, type `sendtype`.
2. Collect all these messages, by all the processes, at position `recvbuf` of `recvcount` element type `recvtype`.

Remarks :

- The couples (`sendcount`, `sendtype`) and (`recvcount`, `recvtype`) must represent the same data size.
- The data are gathered in the order of the process ranks.

Collective communications

Example of MPI_Allgather()

```
1 program allgather
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_values=8
6 integer :: nb_procs,rank,block_length,i
7 real, dimension(nb_values) :: recvdata
8 real, allocatable, dimension(:) :: values
9
10 call MPI_INIT()
11
12 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
13 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
14
15 block_length=nb_values/nb_procs
16 allocate(values(block_length))
17
18 values(:)=(/1000.+rank*block_length+i,i=1,block_length/)
19
20 call MPI_ALLGATHER(values,block_length,MPI_REAL,recvdata,block_length,
21 & MPI_REAL,MPI_COMM_WORLD)
22
23 print *,'I, process ',rank,', received ', recvdata(1:nb_values)
24
25 call MPI_FINALIZE()
26
27 end program allgather
```

```
> mpixec -n 4 allgather

I, process 1, received 1001. 1002. 1003. 1004. 1005. 1006. 1007. 1008.
I, process 3, received 1001. 1002. 1003. 1004. 1005. 1006. 1007. 1008.
I, process 2, received 1001. 1002. 1003. 1004. 1005. 1006. 1007. 1008.
I, process 0, received 1001. 1002. 1003. 1004. 1005. 1006. 1007. 1008.
```

Collective communications

Extended gather : `MPI_Gatherv()`




Figure 17 – Extended gather : `MPI_Gatherv()`

Collective communications

Extended Gather : MPI_Gatherv()

This is an `MPI_Gather()` where the size of messages can be different among processes :

```
MPI_GATHERV(sendbuf, sendcount, sendtype,
             recvbuf, recvcounts, displs, recvtype,
             root, comm, code)

TYPE(*), dimension(..), intent(in) :: sendbuf
TYPE(*), dimension(..)           :: recvbuf
integer, intent(in)              :: sendcount, root
TYPE(MPI_Datatype), intent(in)   :: sendtype, recvtype
integer, dimension(:), intent(in) :: recvcounts, displs
TYPE(MPI_Comm), intent(in)      :: comm
integer, optional, intent(out)   :: code
```

The i-th process of the communicator `comm` sends to process `root`, a message starting at position `sendbuf`, of `sendcount` element of type `sendtype`, and `root` receives at position `recvbuf`, of `recvcounts(i)` element of type `recvtype`, with a displacement of `displs(i)`.

Remarks :

- The couples (`sendcount,sendtype`) of the i-th process and (`recvcounts(i), recvtype`) of process `root` must be such that the data size sent and received is the same.

Collective communications

Example of MPI_Gatherv()

```
1 program gatherv
2 use mpi_f08
3 implicit none
4 INTEGER, PARAMETER :: nb_values=10
5 INTEGER :: nb_procs, rank, block_length, i
6 REAL, DIMENSION(nb_values) :: recvdata, remainder
7 REAL, ALLOCATABLE, DIMENSION(:) :: values
8 INTEGER, ALLOCATABLE, DIMENSION(:) :: nb_elements_received, displacement
9
10 CALL MPI_INIT()
11 CALL MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
12 CALL MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13
14 block_length=nb_values/nb_procs
15 remainder=mod(nb_values,nb_procs)
16 if(rank < remainder) block_length = block_length + 1
17 ALLOCATE(values(block_length))
18 values(:) = (/1000.+(rank*(nb_values/nb_procs))+min(rank,remainder)+i, &
19 i=1,block_length/)
20
21 PRINT *, 'I, process ', rank,' sent my values array : ',&
22 values(1:block_length)
23
24 IF (rank == 2) THEN
25   ALLOCATE(nb_elements_received(nb_procs),displacement(nb_procs))
26   nb_elements_received(1) = nb_values/nb_procs
27   if(remainder > 0) nb_elements_received(1)=nb_elements_received(1)+1
28   displacement(1) = 0
29   DO i=2,nb_procs
30     displacement(i) = displacement(i-1)+nb_elements_received(i-1)
31     nb_elements_received(i) = nb_values/nb_procs
32     if( (i-1 < remainder) nb_elements_received(i)=nb_elements_received(i)+1
33   END DO
34 END IF
```

Collective communications

Example of MPI_Gatherv()

```
35 CALL MPI_GATHERV(values,block_length,MPI_REAL,recvdata,nb_elements_received,&
36           displacement,MPI_REAL,2,MPI_COMM_WORLD)
37 IF (rank == 2) PRINT *, 'I, process 2, received ', recvdata (1:nb_values)
38 CALL MPI_FINALIZE()
39 end program gatherv
```

```
> mpieexec -n 4 gatherv

I, process 0 sent my values array : 1001. 1002. 1003.
I, process 2 sent my values array : 1007. 1008.
I, process 3 sent my values array : 1009. 1010.
I, process 1 sent my values array : 1004. 1005. 1006.

I, process 2 receives 1001. 1002. 1003. 1004. 1005. 1006. 1007. 1008. 1009. 1010.
```

Collective communications

Collection and distribution : `MPI_Alltoall()`




Figure 18 – Collection and distribution :: `MPI_Alltoall()`

Collective communications

Collection and distribution : MPI_Alltoall()

```
MPI_ALLTOALL(sendbuf, sendcount, sendtype,  
             recvbuf, recvcount, recvtype, comm, code)  
  
TYPE(*), dimension(..), intent(in) :: sendbuf  
TYPE(*), dimension(..)           :: recvbuf  
integer, intent(in)              :: sendcount, recvcount  
TYPE(MPI_Datatype), intent(in)   :: sendtype, recvtype  
TYPE(MPI_Comm), intent(in)       :: comm  
integer, optional, intent(out)   :: code
```

Here, the i-th process sends its j-th chunk to the j-th process which places it in its i-th chunk.

Remark :

- The couples (`sendcount`, `sendtype`) and (`recvcount`, `recvtype`) must be such that they represent equal data sizes.

Collective communications

Example of MPI_Alltoall()

```
1 program alltoall
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_values=8
6 integer :: nb_procs,rank,block_length,i
7 real, dimension(nb_values) :: values,recvdata
8
9 call MPI_INIT()
10 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
11 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
12
13 values(:)=(/1000.+rank*nb_values+i,i=1,nb_values/)
14 block_length=nb_values/nb_procs
15
16 print *,'I, process ',rank,' sent my values array : ',&
17 values(1:nb_values)
18
19 call MPI_ALLTOALL(values,block_length,MPI_REAL,recvdata,block_length, &
20 MPI_REAL,MPI_COMM_WORLD)
21
22 print *,'I, process ',rank,', received ', recvdata(1:nb_values)
23
24 call MPI_FINALIZE()
25 end program alltoall
```

Collective communications

Example of MPI_Alltoall()

```
> mpieexec -n 4 alltoall
I, process 1 sent my values array :
1009. 1010. 1011. 1012. 1013. 1014. 1015. 1016.
I, processus 0 sent my values array :
1001. 1002. 1003. 1004. 1005. 1006. 1007. 1008.
I, processus 2 sent my values array :
1017. 1018. 1019. 1020. 1021. 1022. 1023. 1024.
I, processus 3 sent my values array :
1025. 1026. 1027. 1028. 1029. 1030. 1031. 1032.

I, process 0, received 1001. 1002. 1009. 1010. 1017. 1018. 1025. 1026.
I, process 2, received 1005. 1006. 1013. 1014. 1021. 1022. 1029. 1030.
I, process 1, received 1003. 1004. 1011. 1012. 1019. 1020. 1027. 1028.
I, process 3, received 1007. 1008. 1015. 1016. 1023. 1024. 1031. 1032.
```

Global reduction

- A **reduction** is an operation applied to a set of elements in order to obtain one single value. Typical examples are the sum of the elements of a vector (`SUM(A(:))`) or the search for the maximum value element in a vector (`MAX(V(:))`).
- MPI proposes high-level subroutines in order to operate reductions on data distributed on a group of processes. The result is obtained on only one process (`MPI_Reduce()`) or on all the processes (`MPI_Allreduce()`, which is in fact equivalent to an `MPI_Reduce()` followed by an `MPI_Bcast()`).
- If several elements are implied by process, the reduction function is applied to each one of them (for instance to each element of a vector).

Collective communications

Distributed reduction : MPI_Reduce




Figure 19 – Distributed reduction (sum)

Collective communications

Operations

Name	Operation
MPI_SUM	Sum of elements
MPI_PROD	Product of elements
MPI_MAX	Maximum of elements
MPI_MIN	Minimum of elements
MPI_MAXLOC	Maximum of elements and location
MPI_MINLOC	Minimum of elements and location
MPI_LAND	Logical AND
MPI_LOR	Logical OR
MPI_LXOR	Logical exclusive OR

Collective communications

Global reduction : MPI_Reduce ()

```
MPI_REDUCE(sendbuf, recvbuf, count, datatype, op, root, comm, code)

TYPE(*), dimension(..), intent(in) :: sendbuf
TYPE(*), dimension(..)           :: recvbuf
integer, intent(in)              :: count, root
TYPE(MPI_Datatype), intent(in)   :: datatype
TYPE(MPI_Op), intent(in)         :: op
TYPE(MPI_Comm), intent(in)       :: comm
integer, optional, intent(out)   :: code
```

1. Distributed reduction of `count` elements of type `datatype`, starting at position `sendbuf`, with the operation `op` from each process of the communicator `comm`,
2. Return the result at position `recvbuf` in the process `root`.

Collective communications

Example of MPI_Reduce()

```
1 program reduce
2 use mpi_f08
3 implicit none
4 integer :: nb_procs,rank,value,sum
5
6 call MPI_INIT()
7 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
8 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
9
10 if (rank == 0) then
11     value=1000
12 else
13     value=rank
14 endif
15
16 call MPI_REDUCE(value,somme,1,MPI_INTEGER,MPI_SUM,0,MPI_COMM_WORLD)
17
18 if (rank == 0) then
19     print *, 'I, process 0, have the global sum value ',sum
20 end if
21
22 call MPI_FINALIZE()
23 end program reduce
```

```
> mpieexec -n 7 reduce
I, process 0, have the global sum value 1021
```

Collective communications

Distributed reduction with distribution of the result : `MPI_Allreduce()`




Figure 20 – Distributed reduction (product) with distribution of the result

Collective communications

Global all-reduction : `MPI_Allreduce()`

```
MPI_ALLREDUCE(sendbuf, recvbuf, count, datatype, op, comm, code)

TYPE(*), dimension(..), intent(in) :: sendbuf
TYPE(*), dimension(..)           :: recvbuf
integer, intent(in)              :: count
TYPE(MPI_Datatype), intent(in)   :: datatype
TYPE(MPI_Op), intent(in)         :: op
TYPE(MPI_Comm), intent(in)       :: comm
integer, optional, intent(out)   :: code
```

1. Distributed reduction of `count` elements of type `datatype` starting at position `sendbuf`, with the operation `op` from each process of the communicator `comm`,
2. Write the result at position `recvbuf` for all the processes of the communicator `comm`.

Collective communications

Example of MPI_Allreduce()

```
1 program allreduce
2
3 use mpi_f08
4 implicit none
5
6 integer :: nb_procs,rank,value,product
7
8 call MPI_INIT()
9 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
11
12 if (rank == 0) then
13   value=10
14 else
15   value=rank
16 endif
17
18 call MPI_ALLREDUCE(value,product,1,MPI_INTEGER,MPI_PROD,MPI_COMM_WORLD)
19
20 print *,'I,process ',rank,', received the value of the global product ', product
21
22 call MPI_FINALIZE()
23
24 end program allreduce
```

Collective communications

Example of MPI_Allreduce()

```
> mpiexec -n 7 allreduce  
I, process 6, received the value of the global product 7200  
I, process 2, received the value of the global product 7200  
I, process 0, received the value of the global product 7200  
I, process 4, received the value of the global product 7200  
I, process 5, received the value of the global product 7200  
I, process 3, received the value of the global product 7200  
I, process 1, received the value of the global product 7200
```

Collective communications

Additions

- The `MPI_Scan()` subroutine allows making partial reductions by considering, for each process, the previous processes of the communicator and itself.
`MPI_Exscan()` is the *exclusive* version of `MPI_Scan()`, which is *inclusive*.
- The `MPI_Op_create()` and `MPI_Op_free()` subroutines allow personal reduction operations.
- For each reduction operation, the keyword `MPI_IN_PLACE` can be used in order to keep the result in the same place as the sending buffer (but only for the rank(s) that will receive results). Example : call
`MPI_Allreduce(MPI_IN_PLACE, sendrecvbuf, ...).`

Collective communications

Additions

- Similarly to what we have seen for `MPI_Gatherv()` with respect to `MPI_Gather()`, the `MPI_Scatterv()`, `MPI_Allgatherv()` and `MPI_Alltoallv()` subroutines extend `MPI_Scatter()`, `MPI_Allgather()` and `MPI_Alltoall()` to the cases where the processes have different numbers of elements to transmit or gather.
- `MPI_Alltoallw()` is the version of `MPI_Alltoallv()` which enables to deal with heterogeneous elements (by expressing the displacements in bytes and not in elements).

MPI Hands-On – Exercise 3 : Collective communications and reductions

- The aim of this exercise is to compute π by numerical integration. $\pi = \int_0^1 \frac{4}{1+x^2} dx$.
- We use the rectangle method (mean point).
- Let $f(x) = \frac{4}{1+x^2}$ be the function to integrate.
- $nblock$ is the number of points of discretization.
- $width = \frac{1}{nblock}$ the length of discretization and the width of all rectangles.
- Sequential version is available in the `pi.f90` source file.
- You have to do the parallel version with MPI in this file.

Communication Modes

Communication Modes

Point-to-Point Send Modes

Mode	Blocking	Non-blocking
Standard send	<code>MPI_Send()</code>	<code>MPI_Isend()</code>
Synchronous send	<code>MPI_Ssend()</code>	<code>MPI_Issend()</code>
Buffered send	<code>MPI_Bsend()</code>	<code>MPI_Ibsend()</code>
Receive	<code>MPI_Recv()</code>	<code>MPI_Irecv()</code>

Communication Modes

Blocking call

- A call is blocking if the memory space used for the communication can be reused immediately after the exit of the call.
- The data sent can be modified after the call.
- The data received can be read after the call.


Communication Modes

Synchronous sends

A synchronous send involves a synchronization between the involved processes. A send cannot start until its receive is posted. There can be no communication before the two processes are ready to communicate.

Rendezvous Protocol

The rendezvous protocol is generally the protocol used for synchronous sends (implementation-dependent). The return receipt is optional.



Communication Modes

Interface of MPI_Ssend()

```
MPI_SSEND(values, count, msgtype, dest, tag, comm, code)

TYPE(*), dimension(..), intent(in) :: values
integer, intent(in)           :: count, dest, tag
TYPE(MPI_Datatype), intent(in) :: msgtype
TYPE(MPI_Comm), intent(in)   :: comm
integer, optional, intent(out) :: code
```

Advantages of synchronous mode

- Low resource consumption (no buffer)
- Rapid if the receiver is ready (no copying in a buffer)
- Knowledge of receipt through synchronization

Disadvantages of synchronous mode

- Waiting time if the receiver is not there/not ready
- Risk of deadlocks

Communication Modes

Deadlock example

In the following example, there is a deadlock because we are in synchronous mode. The two processes are blocked on the `MPI_Ssend()` call because they are waiting for the `MPI_Recv()` of the other process. However, the `MPI_Recv()` call can only be made after the unblocking of the `MPI_Ssend()` call.

```
1 program ssendrecv
2 use mpi_f08
3 implicit none
4 integer :: rank,value,num_proc
5 integer,parameter :: tag=110
6
7 call MPI_INIT()
8 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
9
10 ! We run on 2 processes
11 num_proc=mod(rank+1,2)
12
13 call MPI_SSEND(rank+1000,1,MPI_INTEGER,num_proc,tag,MPI_COMM_WORLD)
14 call MPI_RECV(value,1,MPI_INTEGER,num_proc,tag,MPI_COMM_WORLD, &
15 MPI_STATUS_IGNORE)
16
17 print *,'I, process',rank,', received',value,'from process',num_proc
18
19 call MPI_FINALIZE()
20 end program ssendrecv
```


Communication Modes

Buffered sends

A buffered send implies the copying of data into an intermediate memory space. There is then no coupling between the two processes of communication. Therefore, the return of this type of send does not mean that the receive has occurred.

Protocol with user buffer on the sender side

In this approach, the buffer is on the sender side and is managed explicitly by the application. A buffer managed by MPI can exist on the receiver side. Many variants are possible. The return receipt is optional.



Communication Modes

Buffered sends

The buffers have to be managed manually (with calls to `MPI_Buffer_attach()` and `MPI_Buffer_detach()`). Message header size needs to be taken into account when allocating buffers (by adding the constant `MPI_BSEND_OVERHEAD()` for each message occurrence).

Interfaces

```
MPI_BUFFER_ATTACH (buf, typesize, code)
MPI_BUFFER_DETACH (buf_adr, typesize, code)

TYPE(*), dimension(..), asynchronous :: buf
TYPE(C_PTR), intent(out)           :: buf_adr
integer                           :: typesize
integer, optional, intent(out)     :: code

MPI_BSEND (values, count, msgtype, dest, tag, comm, code)

TYPE(*), dimension(..), intent(in)   :: values
integer, intent(in)                 :: count, dest, tag
TYPE(MPI_Datatype), intent(in)      :: msgtype
TYPE(MPI_Comm), intent(in)          :: comm
integer, optional, intent(out)      :: code
```

Communication Modes

Advantages of buffered mode

- No need to wait for the receiver (copying in a buffer)
- No risk of deadlocks

Disadvantages of buffered mode

- Uses more resources (memory use by buffers with saturation risk)
- The send buffers in the `MPI_Bsend()` or `MPI_Ibsend()` calls have to be managed manually (often difficult to choose a suitable size)
- Slightly slower than the synchronous sends if the receiver is ready
- No knowledge of receipt (send-receive decoupling)
- Risk of wasted memory space if buffers are too oversized
- Application crashes if buffer is too small
- There are often hidden buffers managed by the MPI implementation on the sender side and/or on the receiver side (and consuming memory resources)

Communication Modes

No deadlocks

In the following example, we don't have a deadlock because we are in buffered mode. After the copy is made in the *buffer*, the `MPI_Bsend()` call returns and then the `MPI_Recv()` call is made.

```
1 program bsendrecv
2 use mpi_f08
3 use, INTRINSIC :: ISO_C_BINDING
4 implicit none
5 integer :: rank,value,num_proc,typesize,overhead,bufsize
6 integer,parameter :: tag=110, nb_elt=1, nb_msg=1
7 integer,dimension(:), allocatable :: buffer
8 type(C_PTR) :: p
9
10 call MPI_INIT()
11 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
12
13 call MPI_TYPE_SIZE(MPI_INTEGER,typesize)
14 ! Convert MPI_BSEND_OVERHEAD (bytes) in number of integer
15 overhead = int(1+(MPI_BSEND_OVERHEAD*1.)/typesize)
16 allocate(buffer(nb_msg*(nb_elt+overhead)))
17 bufsize = typesize*nb_msg*(nb_elt+overhead)
18 call MPI_BUFFER_ATTACH(buffer,bufsize)
19 ! We run on 2 processes
20 num_proc=mod(rank+1,2)
21 call MPI_BSEND(rank+1000,nb_elt,MPI_INTEGER,num_proc,tag,MPI_COMM_WORLD)
22 call MPI_RECV(value,nb_elt,MPI_INTEGER, num_proc,tag,MPI_COMM_WORLD, &
23 MPI_STATUS_IGNORE)
24
25 print *,'I, process', rank,' received', value, 'from process', num_proc
26 call MPI_BUFFER_DETACH(p,bufsize)
27 call MPI_FINALIZE()
28 end program bsendrecv
```

Communication Modes

Standard sends

A standard send is made by calling the `MPI_Send()` subroutine. In most implementations, the mode is buffered (*eager*) for small messages but is synchronous for larger messages.

Interfaces


```
MPI_SEND(values, count, msgtype, dest, tag, comm, code)

TYPE(*), dimension(..), intent(in) :: values
integer, intent(in)           :: count, dest, tag
TYPE(MPI_Datatype), intent(in) :: msgtype
TYPE(MPI_Comm), intent(in)    :: comm
integer, optional, intent(out) :: code
```

Communication Modes

The eager protocol

The eager protocol is often used for standard sends of small-size messages. It can also be used for sends with `MPI_Bsend()` for small messages (implementation-dependent) and by bypassing the user buffer on the sender side. In this approach, the buffer is on the receiver side. The return receipt is optional.



Communication Modes

Advantages of standard mode

- Often the most efficient (because the constructor chose the best parameters and algorithms)

Disadvantages of standard mode

- Little control over the mode actually used (often accessible via environment variables)
- Risk of deadlocks depending on the mode used
- Behavior can vary according to the architecture and problem size

Communication Modes

Number of received elements

```
MPI_RECV(buf,count,datatype,source,tag,comm,msgstatus,code)

TYPE(*), dimension(..)      :: buf
integer                      :: count, source, tag
TYPE(MPI_Datatype), intent(in) :: datatype
TYPE(MPI_Comm), intent(in)   :: comm
TYPE(MPI_Status)             :: msgstatus
integer, optional, intent(out) :: code
```

- In `MPI_Recv()` call, the `count` argument in the standard is the number of elements in the buffer `buf`.
- This number must be greater than the number of elements to be received.
- When it is possible, for increased clarity, it is advised to put the number of elements to be received.
- We can obtain the number of elements received with `MPI_Get_count()` and the `msgstatus` argument returned by the `MPI_Recv()` call.

```
MPI_GET_COUNT(msgstatus,msgtype,count,code)

TYPE(MPI_Status), intent(in)  :: msgstatus
TYPE(MPI_Datatype), intent(in) :: msgtype
integer, intent(out)          :: count
integer, optional, intent(out) :: code
```

Communication Modes

Number of received elements

`MPI_Probe` allow incoming messages to be checked for, without actually receiving them.

```
MPI_PROBE(source,tag,comm,statut,code)

integer, intent(in)          :: source, tag
TYPE(MPI_Comm), intent(in)   :: comm
TYPE(MPI_Status)             :: statut
integer, optional, intent(out) :: code
```

A common use of `MPI_Probe` is to allocate space for a message before receiving it.

```
call MPI_Probe(MPI_ANY_SOURCE, MPI_ANY_TAG, comm, statut)
call MPI_Get_count(statut, MPI_INTEGER, msgsize)
allocate(buf(msgsize))
call MPI_Recv(buf, msgsize, MPI_INTEGER, statut%MPI_SOURCE,
            statut%MPI_TAG, comm, MPI_STATUS_IGNORE)
```

Communication Modes

Presentation

The overlap of communications by computations is a method which allows executing communications operations in the background while the program continues to operate. On Jean Zay, the latency of a communication internode is $1.5 \mu\text{s}$, or 2500 processor cycles.


- It is thus possible, if the hardware and software architecture allows it, to hide all or part of communications costs.
- The computation-communication overlap can be seen as an additional level of parallelism.
- This approach is used in MPI by using nonblocking subroutines (i.e. `MPI_Isend()`, `MPI_Irecv()` and `MPI_Wait()`).

Non blocking communication


A nonblocking call returns very quickly but it does not authorize the immediate re-use of the memory space which was used in the communication. It is necessary to make sure that the communication is fully completed (with `MPI_Wait()`, for example) before using it again.

Communication Modes

Partial overlap



Full overlap



Communication Modes

Advantages of non blocking call

- Possibility of hiding all or part of communications costs (if the architecture allows it)
- No risk of deadlock

Disadvantages of non blocking call

- Greater additional costs (several calls for one single send or receive, request management)
- Higher complexity and more complicated maintenance
- Less efficient on some machines (for example with transfer starting only at the `MPI_Wait()` call)
- Risk of performance loss on the computational kernels (for example, differentiated management between the area near the border of a domain and the interior area, resulting in less efficient use of memory caches)
- Limited to point-to-point communications (it is extended to collective communications in MPI 3.0)

Communication Modes

Interfaces

`MPI_ISEND()` `MPI_ISSEND()` and `MPI_IBSEND()` for nonblocking send

```
MPI_ISEND(values, count, datatype, dest, tag, comm, req, code)
MPI_ISSEND(values, count, datatype, dest, tag, comm, req, code)
MPI_IBSEND(values, count, datatype, dest, tag, comm, req, code)

TYPE(*), dimension(..), intent(in), asynchronous :: values
integer, intent(in) :: count, dest, tag
TYPE(MPI_Datatype), intent(in) :: datatype
TYPE(MPI_Comm), intent(in) :: comm
TYPE(MPI_Request), intent(out) :: req
integer, optional, intent(out) :: code
```

`MPI_IRecv()` for nonblocking receive.

```
MPI_RECV(values, count, msgtype, source, tag, comm, req, code)

TYPE(*), dimension(..), intent(in), asynchronous :: values
integer, intent(in) :: count, source, tag
TYPE(MPI_Datatype), intent(in) :: msgtype
TYPE(MPI_Comm), intent(in) :: comm
TYPE(MPI_Request), intent(out) :: req
integer, optional, intent(out) :: code
```

Communication Modes

Interfaces

`MPI_Wait()` wait for the end of a communication, `MPI_Test()` is the nonblocking version.

```
MPI_WAIT(req, statut, code)
MPI_TEST(req, flag, statut, code)

TYPE(MPI_Request), intent(inout) :: req
logical, intent(out)           :: flag
TYPE(MPI_Status)               :: statut
integer, optional, intent(out) :: code
```

`MPI_Waitall()` (`MPI_Testall()`) await the end of all communications.

```
MPI_WAITALL(count, reqs, statuts, code)
MPI_TESTALL(count, reqs, flag, statuts, code)

integer, intent(in)           :: count
TYPE(MPI_Request), dimension(taille) :: reqs
logical, intent(out)          :: flag
TYPE(MPI_Status), dimension(taille) :: statuts
integer, optional, intent(out) :: code
```

Communication Modes

Interfaces

`MPI_Waitany()` wait for the end of one communication, `MPI_Testany()` is the nonblocking version.

```
MPI_WAITANY(count, reqs, index, msgstatus, code)
MPI_TESTANY(count, reqs, index, flag, msgstatus, code)

integer, intent(in) :: count
TYPE(MPI_Request), dimension(count), intent(inout) :: reqs
integer, intent(out) :: index
logical, intent(out) :: flag
TYPE(MPI_Status) :: msgstatus
integer, optional, intent(out) :: code
```

`MPI_Waitsome()` wait for the end of at least one communication, `MPI_Testsome()` is the nonblocking version.

```
MPI_WAITSOME(count, reqs, outcount, indices, statuses, code)
MPI_TESTSOME(count, reqs, outcount, indices, statuses, code)


integer, intent(in) :: count
TYPE(MPI_Request), dimension(count), intent(inout) :: reqs
integer, intent(out) :: outcount
integer, dimension(count), intent(out) :: indices
TYPE(MPI_Status), dimension(count), intent(out) :: statuses
integer, optional, intent(out) :: code
```

Communication Modes

Request management

- After a call to a blocking wait function (`MPI_Wait()`, `MPI_Waitall()`,...), the request argument is set to `MPI_REQUEST_NULL`.
- The same for a nonblocking wait when the *flag* is set to true.
- A wait call with a `MPI_REQUEST_NULL` request does nothing.

Communication Modes



Communication Modes

```
1 SUBROUTINE start_communication(u)
2     ! Send to the North and receive from the South
3     CALL MPI_IRecv( u(), 1, rowtype, neighbor(S), &
4                     tag, comm2d, request(1))
5     CALL MPI_Isend( u(), 1, rowtype, neighbor(N), &
6                     tag, comm2d, request(2))
7
8     ! Send to the South and receive from the North
9     CALL MPI_IRecv( u(), 1, rowtype, neighbor(N), &
10                    tag, comm2d, request(3))
11    CALL MPI_Isend( u(), 1, rowtype, neighbor(S), &
12                    tag, comm2d, request(4))
13
14    ! Send to the West and receive from the East
15    CALL MPI_IRecv( u(), 1, columntype, neighbor(E), &
16                    tag, comm2d, request(5))
17    CALL MPI_Isend( u(), 1, columntype, neighbor(W), &
18                    tag, comm2d, request(6))
19
20    ! Send to the East and receive from the West
21    CALL MPI_IRecv( u(), 1, columntype, neighbor(W), &
22                    tag, comm2d, request(7))
23    CALL MPI_Isend( u(), 1, columntype, neighbor(E), &
24                    tag, comm2d, request(8))
25 END SUBROUTINE start_communication
26 SUBROUTINE end_communication(u)
27     CALL MPI_Waitall(2*NB_NEIGHBORS,request,tab_status,code)
28     if (.not. MPI_ASYNC_PROTECTS_NONBLOCKING) call MPI_F_SYNC_REG(u)
29 END SUBROUTINE end_communication
```

Communication Modes

```
1 DO WHILE ((.NOT. convergence) .AND. (it < it_max))
2   it = it +1
3   u(sx:ex,sy:ey) = u_new(sx:ex,sy:ey)
4
5   ! Exchange value on the interfaces
6   CALL start_communication( u )
7
8   ! Compute u
9   CALL calcul( u, u_new, sx+1, ex-1, sy+1, ey-1)
10
11  CALL end_communication( u )
12
13  ! North
14  CALL calcul( u, u_new, sx, sx, sy, ey)
15  ! South
16  CALL calcul( u, u_new, ex, ex, sy, ey)
17  ! West
18  CALL calcul( u, u_new, sx, ex, sy, sy)
19  ! East
20  CALL calcul( u, u_new, sx, ex, ey, ey)
21
22  ! Compute global error
23  diffnorm = global_error (u, u_new)
24
25  convergence = ( diffnorm < eps )
26
27 END DO
```

Communication Modes

Overlap levels on different machines

<i>Machine</i>	<i>Level</i>
Zay(IntelMPI)	43%
Zay(IntelMPI) I_MPI_ASYNC_PROGRESS=yes	95%

Measurements taken by overlapping a compute kernel with a communication kernel which have the same execution times.

An overlap of 0% means that the total execution time is twice the time of a compute (or a communication) kernel.

An overlap of 100% means that the total execution time is the same as the time of a compute (or a communication) kernel.

Nonblocking collectives

- Nonblocking version of collective communications
- With an I (**immediate**) before : `MPI_Ireduce()`, `MPI_Ibcast()`, ...
- Wait with `MPI_Wait()`, `MPI_Test()` calls and all their variants
- No match between blocking and nonblocking
- The *status* argument retrieved by `MPI_Wait()` has an undefined value for `MPI_SOURCE` and `MPI_TAG`
- For a given communicator, the call order must be the same

```
MPI_IBARRIER(comm, request, code)

TYPE(MPI_Comm), intent(in)    :: comm,
TYPE(MPI_Request), intent(out) :: request
integer, optional, intent(out) :: code
```

Modèles de communication

Usage example of MPI_Ibarrier

How to manage communications when we don't know at each iteration if our neighbors will send a message.

```
logical isAllFinish=.false.
logical isMySendFinish=.false.
do i=1,m
    ! Synchronous send
    call MPI_ISSEND(sbuf(i),ssize(i),datatype,dst(i),tag,comm,reqs(i))
end do

do while (.not. isAllFinish)
    ! Do we have a message ready to be received
    call MPI_IPROBE(MPI_ANY_SOURCE,tag,comm,flag,astat)
    if (flag) then
        ! Receive the message
        call MPI_RECV(rbuf,rsize,datatype,astat%MPI_SOURCE,tag,comm,rstat)
    end if
    if (.not. isMySendFinish) then
        ! Check if all our ssend are finished
        call MPI_TESTALL(m,reqs,flag,MPI_STATUSES_IGNORE)
        if (flag) then
            ! If yes we start the ibarrier
            call MPI_IBARRIER(comm,reqb)
            isMySendFinish=.true.
        end if
    else
        ! Test if everybody have started the ibarrier
        call MPI_TEST(reqb,isAllFinish,MPI_STATUS_IGNORE)
    end if
end do
```

Communication Modes

MPI-3 functionalities added


- If `MPI_SUBARRAYS_SUPPORTED` is set to *true*, it's possible to use Fortran subarrays in nonblocking calls.
- If `MPI_ASYNC_PROTECTS_NONBLOCKING` is set to *true*, the send and/or receive arguments are *asynchronous* in nonblocking interfaces.

```
call MPI_ISEND(buf,...,req)
...
call MPI_WAIT(req,...)
if (.not. MPI_ASYNC_PROTECTS_NONBLOCKING) call MPI_F_SYNC_REG(buf)
buf = val2
```

Communication Modes

One-Sided Communications

One-sided communications (Remote Memory Access or RMA) consists of accessing the memory of a distant process in *read* or *write* without the distant process having to manage this access explicitly. The target process does not intervene during the transfer.



Communication Modes

General approach

- Creation of a memory window with `MPI_Win_create()` to authorize RMA transfers in this zone.
- Remote access in *read* or *write* by calling `MPI_Put()`, `MPI_Get()`, `MPI_Accumulate()`, `MPI_Fetch_and_op()`, `MPI_Get_accumulate()` and `MPI_Compare_and_swap()`.
- Free the memory window with `MPI_Win_free()`.

Synchronization methods

In order to ensure the correct functioning of the application, it is necessary to execute some synchronizations. Three methods are available :

- Active target communication with global synchronization (`MPI_Win_fence()`)
- Active target communication with synchronization by pair (`MPI_Win_start()` and `MPI_Win_complete()` for the origin process; `MPI_Win_post()` and `MPI_Win_wait()` for the target process)
- Passive target communication without target intervention (`MPI_Win_lock()` and `MPI_Win_unlock()`)

Communication Modes

```
1 program ex_fence
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: assert=0
6 integer :: code, rank, realsize, i, nbelts, targetrank, m=4, n=4
7 type(MPI_Win) :: win
8 integer (kind=MPI_ADDRESS_KIND) :: displacement, dim_win
9 real(kind=kind(1.d0)), dimension(:), allocatable :: win_local, tab
10
11 call MPI_INIT()
12 call MPI_COMM_RANK(MPI_COMM_WORLD, rank)
13 call MPI_TYPE_SIZE(MPI_DOUBLE_PRECISION, realsize)
14
15 if (rank==0) then
16     n=0
17     allocate(tab(m))
18 endif
19
20 allocate(win_local(n))
21 dim_win = realsize*n
22
23 call MPI_WIN_CREATE(win_local, dim_win, realsize, MPI_INFO_NULL, &
24                     MPI_COMM_WORLD, win)
```

Communication Modes

```
25      if (rank==0) then
26          tab(:) = (/ (i, i=1,m) /)
27      else
28          win_local(:) = 0.0
29      end if
30
31      call MPI_WIN_FENCE(assert,win)
32      if (rank==0) then
33          targetrank = 1; nbelts = 2; displacement = 1
34          call MPI_PUT(tab, nbelts, MPI_DOUBLE_PRECISION, targetrank, displacement, &
35                      nbelts, MPI_DOUBLE_PRECISION, win)
36      end if
37
38      call MPI_WIN_FENCE(assert,win)
39      if (rank==0) then
40          tab(m) = sum(tab(1:m-1))
41      else
42          win_local(n) = sum(win_local(1:n-1))
43      endif
44
45      call MPI_WIN_FENCE(assert,win)
46      if (rank==0) then
47          nbelts = 1; displacement = m-1
48          call MPI_GET(tab, nbelts, MPI_DOUBLE_PRECISION, targetrank, displacement, &
49                      nbelts, MPI_DOUBLE_PRECISION, win)
50      end if
```

Communication Modes

Advantages of One-Sided Communications

- Certain algorithms can be written more easily.
- More efficient than point-to-point communications on certain machines (use of specialized hardware such as a DMA engine, coprocessor, specialized memory, ...).
- The implementation can group together several operations.

Disadvantages of One-Sided Communications

- Synchronization management is tricky.
- Complexity and high risk of error.
- Less efficient than point-to-point communications on certain machines.

Derived datatypes

Derived datatypes

Introduction

- In communications, exchanged data have different datatypes : `MPI_INTEGER`, `MPI_REAL`, `MPI_COMPLEX`, etc.
- We can create more complex data structures by using subroutines such as `MPI_Type_contiguous()`, `MPI_Type_vector()`, `MPI_Type_indexed()` or `MPI_Type_create_struct()`
- Derived datatypes allow exchanging non-contiguous or non-homogenous data in the memory and limiting the number of calls to communications subroutines.

Derived datatypes




Figure 21 – Hierarchy of the MPI constructors

Derived datatypes

Contiguous datatypes

- `MPI_Type_contiguous()` creates a data structure from a homogenous set of existing datatypes contiguous in memory.

1.	6.	11.	16.	21.	26.
2.	7.	12.	17.	22.	27.
3.	8.	13.	18.	23.	28.
4.	9.	14.	19.	24.	29.
5.	10.	15.	20.	25.	30.

```
call MPI_TYPE_CONTIGUOUS(5,MPI_REAL,new_type,code)
```

Figure 22 – MPI_Type_contiguous subroutine

```
MPI_TYPE_CONTIGUOUS(count,old_type,new_type,code)

integer, intent(in)          :: count
TYPE(MPI_Datatype), intent(int) :: old_type
TYPE(MPI_Datatype), intent(out) :: new_type
integer, optional, intent(out) :: code
```

Derived datatypes

Constant stride

- `MPI_Type_vector()` creates a data structure from a homogenous set of existing datatypes **separated by a constant stride** in memory. The stride is given in number of **elements**.

1.	6.	11.	16.	21.	26.
2.	7.	12.	17.	22.	27.
3.	8.	13.	18.	23.	28.
4.	9.	14.	19.	24.	29.
5.	10.	15.	20.	25.	30.

```
call MPI_TYPE_VECTOR(6, 1, 5, MPI_REAL, new_type, code)
```

Figure 23 – MPI_Type_vector subroutine

```
MPI_TYPE_VECTOR(count,block_length,stride,old_type,new_type,code)

integer, intent(in) :: count,block_length
integer, intent(in) :: stride ! donne en elements
TYPE(MPI_Datatype), intent(in) :: old_type
TYPE(MPI_Datatype), intent(out) :: new_type
integer, optional, intent(out) :: code
```

Derived datatypes

Constant stride

- `MPI_Type_create_hvector()` creates a data structure from a homogenous set of existing datatype separated by a constant stride in memory. The stride is given in bytes.
- This call is useful when the old type is no longer a base datatype (`MPI_INTEGER`, `MPI_REAL`, ...) but a more complex datatype constructed by using MPI subroutines, because in this case the stride can no longer be given in number of elements.

```
MPI_TYPE_CREATE_HVECTOR(count,block_length,stride,old_type,new_type,code)

integer, intent(in)                      :: count,block_length
integer(kind=MPI_ADDRESS_KIND), intent(in) :: stride ! given in bytes
TYPE(MPI_Datatype), intent(in)            :: old_type
TYPE(MPI_Datatype), intent(out)           :: new_type
integer, optional, intent(out)             :: code
```

Derived datatypes

Commit derived datatypes

- Before using a new derived datatype, it is necessary to validate it with the `MPI_Type_commit()` subroutine.

```
MPI_TYPE_COMMIT(new_type,code)

TYPE(MPI_Datatype), intent(inout) :: new_type
integer, optional, intent(out)   :: code
```

- The freeing of a derived datatype is made by using the `MPI_Type_free()` subroutine.

```
MPI_TYPE_FREE(new_type,code)

TYPE(MPI_Datatype), intent(inout) :: new_type
integer, optional, intent(out)   :: code
```

Derived datatypes

```
1 program column
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_lines=5,nb_columns=6
6 integer, parameter :: tag=100
7 real, dimension(nb_lines,nb_columns) :: a
8 TYPE(MPI_Status) :: msgstatus
9 integer :: rank
10 TYPE(MPI_Datatype) :: type_column
11
12 call MPI_INIT()
13 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
14
15 ! Initialization of the matrix on each process
16 a(:, :) = real(rank)
17
18 ! Definition of the type_column datatype
19 call MPI_TYPE_CONTIGUOUS(nb_lines,MPI_REAL,type_column)
20
21 ! Validation of the type_column datatype
22 call MPI_TYPE_COMMIT(type_column)
```

Derived datatypes

```
23 ! Sending of the first column
24 if ( rank == 0 ) then
25   call MPI_SEND(a(1,1),1,type_column,1,tag,MPI_COMM_WORLD)
26
27 ! Reception in the last column
28 elseif ( rank == 1 ) then
29   call MPI_RECV(a(1,nb_columns),nb_lines,MPI_REAL,0,tag,&
30                 MPI_COMM_WORLD, msgstatus)
31 end if
32
33 ! Free the datatype
34 call MPI_TYPE_FREE(type_column)
35
36 call MPI_FINALIZE()
37
38 end program column
```

Derived datatypes

```
1 program line
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_lines=5,nb_columns=6
6 integer, parameter :: tag=100
7 real, dimension(nb_lines,nb_columns) :: a
8 TYPE(MPI_Status) :: msgstatus
9 integer :: rank
10 TYPE(MPI_Datatype) :: type_line
11
12 call MPI_INIT()
13 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
14
15 ! Initialization of the matrix on each process
16 a(:, :) = real(rank)
17
18 ! Definition of the datatype type_line
19 call MPI_TYPE_VECTOR(nb_columns,1,nb_lines,MPI_REAL,type_line)
20
21 ! Validation of the datatype type_line
22 call MPI_TYPE_COMMIT(type_line)
```

Derived datatypes

```
23 ! Sending of the second line
24 if ( rank == 0 ) then
25   call MPI_SEND(a(2,1),nb_columns,MPI_REAL,1,tag,MPI_COMM_WORLD)
26
27 ! Reception in the next to last line
28 elseif ( rank == 1 ) then
29   call MPI_RECV(a(nb_lines-1,1),1,type_line,0,tag,&
30                 MPI_COMM_WORLD, msgstatus)
31 end if
32
33 ! Free the datatype type_line
34 call MPI_TYPE_FREE(type_line)
35
36 call MPI_FINALIZE()
37
38 end program line
```

Derived datatypes

```
1 program block
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_lines=5,nb_columns=6
6 integer, parameter :: tag=100
7 integer, parameter :: nb_lines_block=2,nb_columns_block=3
8 real, dimension(nb_lines,nb_columns) :: a
9 type(MPI_Status) :: msgstatus
10 integer :: rank
11 type(MPI_Datatype) :: type_block
12
13 call MPI_INIT()
14 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
15
16 ! Initialization of the matrix on each process
17 a(:, :) = real(rank)
18
19 ! Creation of the datatype type_bloc
20 call MPI_TYPE_VECTOR(nb_columns_block,nb_lines_block,nb_lines,&
21 MPI_REAL,type_block)
22
23 ! Validation of the datatype type_bloc
24 call MPI_TYPE_COMMIT(type_block)
```

Derived datatypes

```
25 ! Sending of a block
26 if ( rank == 0 ) then
27   call MPI_SEND(a(1,1),1,type_block,1,tag,MPI_COMM_WORLD)
28
29 ! Reception of the block
30 elseif ( rank == 1 ) then
31   call MPI_RECV(a(nb_lines-1,nb_columns-2),1,type_block,0,tag,&
32                 MPI_COMM_WORLD, msgstatus)
33 end if
34
35 ! Freeing of the datatype type_block
36 call MPI_TYPE_FREE(type_block)
37
38 call MPI_FINALIZE()
39
40 end program block
```

Derived datatypes

Homogenous datatypes of variable strides

- `MPI_Type_indexed()` allows creating a data structure composed of a sequence of blocks containing a variable number of elements separated by a variable stride in memory. The stride is given in number of `elements`.

- `MPI_Type_create_hindexed()` has the same functionality as `MPI_Type_indexed()` except that the strides separating two data blocks are given in `bytes`.

This subroutine is useful when the old datatype is not an MPI base datatype(`MPI_INTEGER`, `MPI_REAL`, ...). We cannot therefore give the stride in number of elements of the old datatype.

- For `MPI_Type_create_hindexed()`, as for `MPI_Type_create_hvector()`, use `MPI_Type_size()` or `MPI_Type_get_extent()` in order to obtain in a portable way the size of the stride in bytes.

Derived datatypes

$\text{nb}=3$, $\text{blocks_lengths}=(2,1,3)$, $\text{displacements}=(0,3,7)$



Figure 24 – The `MPI_Type_indexed` constructor

```
MPI_TYPE_INDEXED(nb,block_lengths,displacements,old_type,new_type,code)

integer,intent(in) :: nb
integer,intent(in),dimension(nb) :: block_lengths
! Attention the displacements are given in elements
integer,intent(in),dimension(nb) :: displacements
TYPE(MPI_Datatype), intent(in) :: old_type
TYPE(MPI_Datatype), intent(out) :: new_type
integer, optional, intent(out) :: code
```

Derived datatypes

nb=4, blocks_lengths=(2,1,2,1), displacements=(2,10,14,24)



Figure 25 – The `MPI_Type_create_hindexed` constructor

```
MPI_TYPE_CREATE_HINDEXED(nb, block_lengths,displacements,  
old_type,new_type,code)  
  
integer,intent(in) :: nb  
integer,intent(in),dimension(nb) :: block_lengths  
! Attention the displacements are given in bytes  
integer(kind=MPI_ADDRESS_KIND),intent(in),dimension(nb) :: displacements  
TYPE(MPI_Datatype), intent(in) :: old_type  
TYPE(MPI_Datatype), intent(out) :: new_type  
integer, optional, intent(out) :: code
```

Derived datatypes

Example : triangular matrix

In the following example, each of the two processes :

1. Initializes its matrix (positive growing numbers on process 0 and negative decreasing numbers on process 1).
2. Constructs its datatype : triangular matrix (superior for the process 0 and inferior for the process 1).
3. Sends its triangular matrix to the other process and receives back a triangular matrix which it stores in the same place which was occupied by the sent matrix.
This is done with the `MPI_Sendrecv_replace()` subroutine.
4. Frees its resources and exits MPI.

Derived datatypes

BEFORE

Processus 0

1	9	17	25	33	41	49	57
2	10	18	26	34	42	50	58
3	11	19	27	35	43	51	59
4	12	20	28	36	44	52	60
5	13	21	29	37	45	53	61
6	14	22	30	38	46	54	62
7	15	23	31	39	47	55	63
8	16	24	32	40	48	56	64

Processus 1

-1	-9	-17	-25	-33	-41	-49	-57
-2	-10	-18	-26	-34	-42	-50	-58
-3	-11	-19	-27	-35	-43	-51	-59
-4	-12	-20	-28	-36	-44	-52	-60
-5	-13	-21	-29	-37	-45	-53	-61
-6	-14	-22	-30	-38	-46	-54	-62
-7	-15	-23	-31	-39	-47	-55	-63
-8	-16	-24	-32	-40	-48	-56	-64

AFTER

1	-2	-3	-5	-8	-14	-22	-32
2	10	-4	-6	-11	-15	-23	-38
3	11	19	-7	-12	-16	-24	-39
4	12	20	28	-13	-20	-29	-40
5	13	21	29	37	-21	-30	-47
6	14	22	30	38	46	-31	-48
7	15	23	31	39	47	55	-56
8	16	24	32	40	48	56	64

-1	-9	-17	-25	-33	-41	-49	-57
9	-10	-18	-26	-34	-42	-50	-58
17	34	-19	-27	-35	-43	-51	-59
18	35	44	-28	-36	-44	-52	-60
25	36	45	52	-37	-45	-53	-61
26	41	49	53	58	-46	-54	-62
27	42	50	54	59	61	-55	-63
33	43	51	57	60	62	63	-64

Derived datatypes

```
1 program triangle
2 use mpi_f08
3 implicit none
4 integer,parameter :: n=8,tag=100
5 real,dimension(n,n) :: a
6 TYPE(MPI_Status) :: msgstatus
7 integer :: i
8 integer :: rank
9 TYPE(MPI_Datatype) :: type_triangle
10 integer,dimension(n) :: block_lengths,displacements
11
12 call MPI_INIT()
13 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
14
15 ! Initialization of the matrix on each process
16 a(:,:) = reshape( (/ (sign(i,-rank),i=1,n*n) /), (/n,n/))
17
18 ! Creation of the triangular matrix datatype sup for process 0
19 ! and of the inferior triangular matrix datatype for process 1
20 if (rank == 0) then
21   block_lengths(:) = (/ (i-1,i=1,n) /)
22   displacements(:) = (/ (n*(i-1),i=1,n) /)
23 else
24   block_lengths(:) = (/ (n-i,i=1,n) /)
25   displacements(:) = (/ (n*(i-1)+i,i=1,n) /)
26 endif
27
28 call MPI_TYPE_INDEXED(n, block_lengths,displacements,MPI_REAL,type_triangle)
29 call MPI_TYPE_COMMIT(type_triangle)
30
31 ! Permutation of the inferior and superior triangular matrices
32 call MPI_SENDRECV_REPLACE(a,1,type_triangle,mod(rank+1,2),tag,mod(rank+1,2), &
33                           tag,MPI_COMM_WORLD,msgstatus)
34
35 ! Freeing of the triangle datatype
36 call MPI_TYPE_FREE(type_triangle)
37 call MPI_FINALIZE()
38 end program triangle
```

Derived datatypes

Size of datatype

- `MPI_Type_size()` returns the number of bytes needed to send a datatype. This value ignores any holes present in the datatype.

```
MPI_TYPE_SIZE(datatype, typesize, code)

TYPE(MPI_Datatype), intent(in) :: datatype
integer, intent(out)      :: typesize
integer, optional, intent(out) :: code
```

- The extent of a datatype is the memory space occupied by this datatype (in bytes). This value is used to calculate the position of the next datatype element (i.e. the stride between two successive datatype elements).

```
MPI_TYPE_GET_EXTENT(datatype, lb, extent, code)

TYPE(MPI_Datatype), intent(in)          :: datatype
integer(kind=MPI_ADDRESS_KIND), intent(out) :: lb, extent
integer, optional, intent(out)          :: code
```

Derived datatypes

Example 1 : `MPI_Type_indexed(2, (/2,1/), (/1,4/), MPI_INTEGER, type, code)`

Derived datatype :



Two successive elements : `[1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10]`

`size = 12` (3 integers); `lb = 4` (1 integer); `extent = 16` (4 integers)

Example 2 : `MPI_Type_vector(3,1,nb_lines, MPI_INTEGER, type_half_line, code)`

2D View :

1	6	11	16	21	26
2	7	12	17	22	27
3	8	13	18	23	28
4	9	14	19	24	29
5	10	15	20	25	30

1D View :



`size = 12` (3 integers); `lb = 0`; `extent = 44` (11 integers)

Derived datatypes

Modify the extent

- The extent is a datatype parameter. By default, it's the space in memory between the first and last component of a datatype (bounds included and with alignment considerations). We can modify the extent to create a new datatype by adapting the preceding one using `MPI_Type_create_resized()`. This provides a way to choose the stride between two successive datatype elements.

```
MPI_TYPE_CREATE_RESIZED(old,lb,extent,new,code)

TYPE(MPI_Datatype), intent(in) :: old
integer(kind=MPI_ADDRESS_KIND), intent(in) :: lb,extent
TYPE(MPI_Datatype), intent(out) :: new
integer, optional, intent(out) :: code
```

Derived datatypes

```
1 program half_line
2 USE mpi_f08
3 IMPLICIT NONE
4 INTEGER,PARAMETER :: nb_lines=5,nb_columns=6,&
5                         half_line_size=nb_columns/2,tag=1000
6 INTEGER,DIMENSION(nb_lines,nb_columns) :: A
7 TYPE(MPI_Datatype) :: typeHalfLine,typeHalfLine2
8 INTEGER :: size_integer,rank,i
9 INTEGER(kind=MPI_ADDRESS_KIND) :: lb=0, extent,sizeDisplacement
10 TYPE(MPI_Status) :: msgstatus
11
12 CALL MPI_INIT()
13 CALL MPI_COMM_RANK(MPI_COMM_WORLD,rank)
14
15 !Initialization of the A matrix on each process
16 A(:,:) = RESHAPE( (/ ($IGN(i,-rank),i=1,nb_lines*nb_columns) /), &
17                   (/ nb_lines,nb_columns /) )
18
19 !Construction of the derived datatype typeHalfLine
20 CALL MPI_TYPE_VECTOR(half_line_size,1,nb_lines,MPI_INTEGER,typeHalfLine)
21
22 !Know the size of the datatype MPI_INTEGER
23 CALL MPI_TYPE_SIZE(MPI_INTEGER, size_integer)
24
25 ! Information on type typeHalfLine
26 call MPI_TYPE_GET_EXTENT(typeHalfLine,lb,extent)
27 if (rank == 0) print *, "typeHalfLine: lb=",lb,", extent=",extent
28
29 !Construction of the derived datatype typeHalfLine2
30 sizeDisplacement = size_integer
31 CALL MPI_TYPE_CREATE_RESIZED(typeHalfLine,lb,sizeDisplacement,&
32                           typeHalfLine2)
```

Derived datatypes

```
33 ! Information on type typeHalfLine2
34 call MPI_TYPE_GET_EXTENT(typeHalfLine2,lb,extent)
35 if (rank == 0) print *, "typeHalfLine2: lb=",lb,", extent=",extent
36
37 !Validation of the datatype typeHalfLine2
38 CALL MPI_TYPE_COMMIT(typeHalfLine2)
39
40 IF (rank == 0) THEN
41 !Sending of the A matrix to the process 1 with the derived datatype typeHalfLine2
42 CALL MPI_SEND(A(1,1), 2, typeHalfLine2, 1, tag, &
43 MPI_COMM_WORLD)
44
45 ELSE
46 !Reception for the process 1 in the A matrix
47 CALL MPI_RECV(A(1,nb_columns-1), 6, MPI_INTEGER, 0, tag,&
48 MPI_COMM_WORLD, msgstatus)
49 PRINT *,'A matrix on the process 1'
50 DO i=1,nb_lines
51 PRINT *,A(i,:)
52 END DO
53
54 CALL MPI_FINALIZE()
55 END PROGRAM half_line
```

```
> mpiexec -n 2 half_line
typeHalfLine: lb=0, extent=44
typeHalfLine2: lb=0, extent=4
```

A matrix on the process 1


-1	-6	-11	-16	1	12
-2	-7	-12	-17	6	-27
-3	-8	-13	-18	11	-28
-4	-9	-14	-19	2	-29
-5	-10	-15	-20	7	-30

Derived datatypes

Heterogenous datatype

- `MPI_Type_create_struct()` call allows creating a set of data blocks indicating the **type**, the **count** and the **displacement** of each block.
- It is the most general datatype constructor. It further generalizes `MPI_Type_indexed()` by allowing a different datatype for each block.

`nb=5, blocks_lengths=(3,1,5,1,1), displacements=(0,7,11,21,26),
old_types=(type1,type2,type3,type1,type3)`



```
MPI_TYPE_CREATE_STRUCT(nb,blocks_lengths,displacements,  
                      old_types,new_type,code)

integer,intent(in) :: nb  
integer,intent(in), dimension(nb) :: blocks_lengths  
integer(kind=MPI_ADDRESS_KIND), intent(in), dimension(nb) :: displacements  
TYPE(MPI_Datatype), intent(in), dimension(nb) :: old_types  
TYPE(MPI_Datatype), intent(out) :: new_type  
integer, optional, intent(out) :: code
```

Derived datatypes

Compute displacements

- `MPI_Type_create_struct()` is useful for creating MPI datatypes corresponding to Fortran derived datatypes or to C structures.
- The memory alignment of heterogeneous data structures is different for each architecture and each compiler.
- Warning, you have to check the extent of the MPI datatypes obtained.
- `MPI_Get_address()` provides the address of a variable. It's equivalent of & operator in C.
- Warning, even in C, it is better to use this subroutine for portability reasons.
- It's advised to use `MPI_Aint_add()` and `MPI_Aint_diff()` to add or subtract addresses.

```
MPI_GET_ADDRESS(variable,address_variable,code)
TYPE(*), dimension(..), asynchronous      :: variable
integer(kind=MPI_ADDRESS_KIND), intent(out) :: address_variable
integer, optional, intent(out)             :: code

integer(KIND=MPI_ADDRESS_KIND) MPI_AINT_ADD(addr1, addr2)
integer(KIND=MPI_ADDRESS_KIND) MPI_AINT_DIFF(addr1, addr2)

integer(KIND=MPI_ADDRESS_KIND)           :: addr1, addr2
```

Derived datatypes

```
1 program Interaction_Particles
2
3 use mpi_f08
4 implicit none
5
6 integer, parameter :: n=1000,tag=100
7 integer, dimension(MPI_STATUS_SIZE) :: msgstatus
8 integer :: rank,i
9 TYPE(MPI_Datatype) :: type_particle
10 TYPE(MPI_Datatype), dimension(4) :: types
11 integer, dimension(4) :: blocks_lengths
12 integer(kind=MPI_ADDRESS_KIND), dimension(5) :: displacements,addresses
13 integer(kind=MPI_ADDRESS_KIND) :: lb,extent
14
15 type Particule
16   character(len=5) :: category
17   integer :: mass
18   real, dimension(3) :: coords
19   logical :: class
20 end type Particule
21 type(Particule), dimension(n) :: p,temp_p
22
23 call MPI_INIT()
24 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
25
26 ! Construction of the datatype
27 types = (/MPI_CHARACTER,MPI_INTEGER,MPI_REAL,MPI_LOGICAL/)
28 blocks_lengths= (/5,1,3,1/)
```

Derived datatypes

```
29      call MPI_GET_ADDRESS(p(1),addresses(1))
30      call MPI_GET_ADDRESS(p(1)%category,addresses(2))
31      call MPI_GET_ADDRESS(p(1)%mass,addresses(3))
32      call MPI_GET_ADDRESS(p(1)%coords,addresses(4))
33      call MPI_GET_ADDRESS(p(1)%class,addresses(5))
34      ! Calculation of displacements relative to the start address
35      do i=1,4
36          displacements(i)=MPI_AINT_DIFF(addresses(i+1),addresses(1))
37      end do
38      call MPI_TYPE_CREATE_STRUCT(4,blocks_lengths,displacements,types,temp)
39      call MPI_GET_ADDRESS(p(2),addresses(2))
40      lb = 0
41      extent = MPI_AINT_DIFF(addresses(2),addresses(1))
42      call MPI_TYPE_CREATE_RESIZED(temp,lb,extent,type_particle)
43      ! Validation of the structured datatype
44      call MPI_TYPE_COMMIT(type_particle)
45      ! Initialization of particles for each process
46      ....
47      ! Sending of particles from 0 towards 1
48      if (rank == 0) then
49          call MPI_SEND(p(1),n,type_particle,1,tag,MPI_COMM_WORLD)
50      else
51          call MPI_RECV(temp_p(1),n,type_particle,0,tag,MPI_COMM_WORLD, &
52                         msgstatus)
53      endif
54
55      ! Freeing of the datatype
56      call MPI_TYPE_FREE(type_particle)
57      call MPI_FINALIZE()
58  end program Interaction_Particles
```

Derived datatypes

Conclusion

- The MPI derived datatypes are powerful data description portable mechanisms.
- When they are combined with subroutines like `MPI_Sendrecv()`, they allow simplifying the writing of interprocess exchanges.
- The combination of derived datatypes and topologies (described in one of the next chapters) makes MPI the ideal tool for all domain decomposition problems with both regular or irregular meshes.

Derived datatypes

Memento

Subroutines	blocks_lengths	strides	old_types
<code>MPI_TypeContiguous()</code>	<code>constant*</code>	<code>constant*</code>	<code>constant</code>
<code>MPI_Type[Create_H]Vector()</code>	<code>constant</code>	<code>constant</code>	<code>constant</code>
<code>MPI_Type[Create_H]Indexed()</code>	<code>variable</code>	<code>variable</code>	<code>constant</code>
<code>MPI_TypeCreateStruct()</code>	<code>variable</code>	<code>variable</code>	<code>variable</code>

(*) hidden parameter, equal to 1

MPI Hands-On – Exercise 4 : Matrix transpose

- The goal of this exercise is to practice with the derived datatypes.
- A is a matrix with 5 lines and 4 columns defined on the process 0.
- Process 0 sends its A matrix to process 1 and transposes this matrix during the send.

1.	6.	11.	16.
2.	7.	12.	17.
3.	8.	13.	18.
4.	9.	14.	19.
5.	10.	15.	20.

Processus 0



1.	2.	3.	4.	5.
6.	7.	8.	9.	10.
11.	12.	13.	14.	15.
16.	17.	18.	19.	20.

Processus 1

- To do this, we need to create two derived datatypes, a derived datatype `type_line` and a derived datatype `type_transpose`.

MPI Hands-On – Exercise 5 : Matrix-matrix product

- Collective communications : matrix-matrix product $C = A \times B$
 - The matrixes are square and their sizes are a multiple of the number of processes.
 - The matrixes A and B are defined on process 0. Process 0 sends a horizontal slice of matrix A and a vertical slice of matrix B to each process. Each process then calculates its diagonal block of matrix C .
 - To calculate the non-diagonal blocks, each process sends to the other processes its own slice of A .
 - At the end, process 0 gathers and verifies the results.

MPI Hands-On – Exercise 5 : Matrix-matrix product




Figure 26 – Distributed matrix product

MPI Hands-On – Exercise 5 : Matrix-matrix product

- The algorithm that may seem the most immediate and the easiest to program, consisting of each process sending its slice of its matrix A to each of the others, does not perform well because the communication algorithm is not well-balanced. It is easy to see this when doing performance measurements and graphically representing the collected traces.




Figure 27 – Parallel matrix product on 16 processes, for a matrix size of 1024 (first algorithm)

MPI Hands-On – Exercise 5 : Matrix-matrix product

- Changing the algorithm in order to *shift* slices from process to process, we obtain a perfect balance between calculations and communications and have a speedup of 2 compared to the naive algorithm.



Figure 28 – Parallel matrix product on 16 processes, for a matrix size of 1024 (second algorithm)

Communicators

Communicators

Introduction

The purpose of communicators is to create subgroups on which we can carry out operations such as collective or point-to-point communications. Each subgroup will have its own communication space.




Figure 29 – Communicator partitioning

Example

For example, we want to broadcast a collective message to even-ranked processes and another message to odd-ranked processes.

- Looping on *send/recv* can be very detrimental especially if the number of processes is high. Also a test inside the loop would be compulsory in order to know if the sending process must send the message to an even or odd process rank.
- A solution is to create a communicator containing the even-ranked processes, another containing the odd-ranked processes, and initiate the collective communications inside these groups.

Default communicator

- A communicator can only be created from another communicator. The first one will be created from the `MPI_COMM_WORLD`.
- After the `MPI_Init()` call, a communicator is created for the duration of the program execution.
- Its identifier `MPI_COMM_WORLD` is a variable defined in the header files.
- This communicator can only be destroyed via a call to `MPI_Finalize()`.
- By default, therefore, it sets `the scope` of collective and point-to-point communications `to include all the processes` of the application.

Communicators

Groups and communicators

- A communicator consists of :
 - A **group**, which is an ordered group of processes.
 - A communication **context** put in place by calling one of the communicator construction subroutines, which allows determination of the communication space.
- The communication contexts are managed by MPI (the programmer has no action on them : It is a hidden attribute).
- In the MPI library, the following subroutines exist for the purpose of building communicators : `MPI_Comm_create()` , `MPI_Comm_dup()` , `MPI_Comm_split()`
- The **communicator constructors** are **collective calls**.
- Communicators created by the programmer can be destroyed by using the `MPI_Comm_free()` subroutine.

Communicators

Partitioning of a communicator

In order to solve the problem example :

- Partition the communicator into odd-ranked and even-ranked processes.
- Broadcast a message inside the odd-ranked processes and another message inside the even-ranked processes.




Figure 30 – Communicator creation/destruction

Communicators

Partitioning of a communicator with `MPI_Comm_split()`

The `MPI_Comm_split()` subroutine allows :

- Partitioning a given communicator into as many communicators as we want.
- Giving the same name to all these communicators : The process value will be the value of its communicator.
- Method :
 1. Define a colour value for each process, associated with its communicator number.
 2. Define a key value for ordering the processes in each communicator
 3. Create the partition where each communicator is called `new_comm`

```
MPI_COMM_SPLIT(comm,color,key,new_comm,code)

TYPE(MPI_Comm), intent(in)      :: comm
integer, intent(in)              :: color, key
TYPE(MPI_Comm), intent(out)     :: new_comm
integer, optional, intent(out)   :: code
```

A process which assigns a color value equal to `MPI_UNDEFINED` will have the invalid communicator `MPI_COMM_NULL` for `new_com`.

Communicators

Example

Let's look at how to proceed in order to build the communicator which will subdivide the communication space into odd-ranked and even-ranked processes via the `MPI_Comm_split()` constructor.

process	a	b	c	d	e	f	g	h
rank_world	0	1	2	3	4	5	6	7
color	0	1	0	1	0	1	0	1
key	0	1	-1	3	4	-1	6	7
rank_even_odd	1	1	0	2	2	0	3	3





Figure 31 – Construction of the `ComEvenOdd` communicator with `MPI_Comm_split()`

Communicators

```
1 program EvenOdd
2   use mpi_f08
3   implicit none
4
5   integer, parameter :: m=16
6   integer :: key
7   TYPE(MPI_Comm) :: CommEvenOdd
8   integer :: rank_in_world
9   real, dimension(m) :: a
10
11  call MPI_INIT()
12  call MPI_COMM_RANK(MPI_COMM_WORLD,rank_in_world)
13
14 ! Initialization of the A vector
15 a(:)=0.
16 if(rank_in_world == 2) a(:)=2.
17 if(rank_in_world == 5) a(:)=5.
18
19 key = rank_in_world
20 if (rank_in_world == 2 .OR. rank_in_world == 5 ) then
21   key=-1
22 end if
23
24 ! Creation of even and odd communicators by giving them the same name
25 call MPI_COMM_SPLIT(MPI_COMM_WORLD,mod(rank_in_world,2),key,CommEvenOdd)
26
27 ! Broadcast of the message by the rank process 0 of each communicator to the processes
28 ! of its group
29 call MPI_BCAST(a,m,MPI_REAL,0,CommEvenOdd)
30
31 ! Destruction of the communicators
32 call MPI_COMM_FREE(CommEvenOdd)
33 call MPI_FINALIZE()
34 end program EvenOdd
```



Communicators

Topologies

- In most applications, especially in domain decomposition methods where we match the calculation domain to the process grid, it is helpful to be able to arrange the processes according to a regular topology.
- MPI allows defining virtual cartesian or graph topologies.
 - Cartesian topologies :
 - ▶ Each process is defined in a grid.
 - ▶ Each process has a neighbour in the grid.
 - ▶ The grid can be periodic or not.
 - ▶ The processes are identified by their coordinates in the grid.
 - Graph topologies :
 - ▶ Can be used in more complex topologies.

1	3	5	7
0	2	4	6




Figure 32 – A 2D Cartesian topology (left) and a Graph topology (right)

Communicators

Cartesian topologies

- A Cartesian topology is defined from a given communicator named `comm_old`, calling the `MPI_Cart_create()` subroutine.
- We define :
 - An integer `ndims` representing the number of grid dimensions.
 - An integer array `dims` of dimension `ndims` showing the number of processes in each dimension.
 - An array of `ndims` logicals which shows the periodicity of each dimension.
 - A logical reorder which shows if the process numbering can be changed by MPI.

```
MPI_CART_CREATE(comm_old, ndims,dims,periods,reorder,comm_new,code)

TYPE(MPI_Comm), intent(in)          :: comm_old
integer, intent(in)                 :: ndims
integer, dimension(ndims), intent(in) :: dims
logical, dimension(ndims), intent(in) :: periods
logical, intent(in)                 :: reorganization
TYPE(MPI_Comm), intent(out)         :: comm_new
integer, optional, intent(out)       :: code
```

Communicators

Example

Example on a grid having 4 domains along x and 2 along y, periodic in y.

```
use mpi_f08
integer :: comm_2D
integer, parameter :: ndims = 2
integer, dimension(ndims) :: dims
logical, dimension(ndims) :: periods
logical :: reorder

.....
dims(1) = 4
dims(2) = 2
periods(1) = .false.
periods(2) = .true.
reorder = .false.

call MPI_CART_CREATE(MPI_COMM_WORLD,ndims,dims,periods,reorder,comm_2D)
```

If `reorder = .false.`, then the rank of the processes in the new communicator (`comm_2D`) is the same as in the old communicator (`MPI_COMM_WORLD`).

If `reorder = .true.`, the MPI implementation chooses the order of the processes.

Communicators




Figure 33 – A 2D periodic Cartesian topology in y

Communicators

3D Example

Example on a 3D grid having 4 domains along x, 2 along y and 2 along z, non periodic.

```
use mpi_f08
TYPE(MPI_Comm)           :: comm_3D
integer, parameter        :: ndims = 3
integer, dimension(ndims) :: dims
logical, dimension(ndims) :: periods
logical                  :: reorder

.....
dims(1) = 4
dims(2) = 2
dims(3) = 2
periods(:) = .false.
reorder = .false.

call MPI_CART_CREATE(MPI_COMM_WORLD,ndims,dims,periods,reorder,comm_3D)
```

Communicators




Figure 34 – A 3D non-periodic Cartesian topology

Communicators

Process distribution

The `MPI_Dims_create()` subroutine returns the number of processes in each dimension of the grid according to the total number of processes.

```
MPI_DIMS_CREATE(nb_procs,ndims,dims,code)

integer, intent(in)          :: nb_procs, ndims
integer, dimension(ndims), intent(inout) :: dims
integer, optional, intent(out)   :: code
```

Remark : If the values of `dims` in entry are all 0, then we leave to MPI the choice of the number of processes in each direction according to the total number of processes.

dims in entry	call <code>MPI_Dims_create</code>	dims en exit
(0,0)	(8,2,dims,code)	(4,2)
(0,0,0)	(16,3,dims,code)	(4,2,2)
(0,4,0)	(16,3,dims,code)	(2,4,2)
(0,3,0)	(16,3,dims,code)	error

Communicateurs

Rank and coordinates of a process

In a Cartesian topology, the rank of each process is associated with its coordinates in the grid.




Figure 35 – A 2D periodic Cartesian topology in y

Rank of a process

In a Cartesian topology, the `MPI_Cart_rank()` subroutine returns the rank of the associated process to the coordinates in the grid.

```
MPI_CART_RANK(comm,coords,rank,code)

TYPE(MPI_Comm), intent(in)          :: comm
integer, dimension(ndims),intent(in) :: coords
integer, intent(out)                :: rank
integer, optional, intent(out)      :: code
```

Communicators




Figure 36 – A 2D periodic Cartesian topology in y

```
coords(1)=dims(1)-1
do i=0,dims(2)-1
  coords(2) = i
  call MPI_CART_RANK(comm_2D,coords,rank(i))
end do
.....
i=0,in entry coords=(3,0),in exit rank(0)=6.
i=1,in entry coords=(3,1),in exit rank(1)=7.
```

Communicators

Coordinates of a process

In a cartesian topology, the `MPI_Cart_coords()` subroutine returns the coordinates of a process of a given rank in the grid.

```
MPI_CART_COORDS(comm, rank, ndims, coords, code)

TYPE(MPI_Comm), intent(in)          :: comm
integer, intent(in)                 :: rank, ndims
integer, dimension(ndims), intent(out) :: coords
integer, optional, intent(out)       :: code
```

Communicators




Figure 37 – A 2D periodic Cartesian topology in y

```
if (mod(rank,2) == 0) then
    call MPI_CART_COORDS(comm_2D,rank,2,coords)
end if
.....
In entry, the rank values are : 0,2,4,6.
In exit, the coords values are :
(0,0),(1,0),(2,0),(3,0)
```

Rank of neighbours

In a Cartesian topology, a process that calls the `MPI_Cart_shift()` subroutine can obtain the rank of a neighboring process in a given direction.

```
MPI_CART_SHIFT(comm, direction, step, rank_previous, rank_next, code)

TYPE(MPI_Comm), intent(in)      :: comm
integer, intent(in)              :: direction, step
integer, intent(out)             :: rank_previous,rank_next
integer, optional, intent(out)   :: code
```

- The `direction` parameter corresponds to the displacement axis (xyz).
- The `step` parameter corresponds to the displacement step.
- If a rank does not have a neighbor before (or after) in the requested direction, then the value of the previous (or following) rank will be `MPI_PROC_NULL`.

Communicators




Figure 38 – Call of the MPI_Cart_shift() subroutine

```
call MPI_CART_SHIFT(comm_2D,0,1,rank_left,rank_right)
.....
For the process 2, rank_left=0, rank_right=4
```

```
call MPI_CART_SHIFT(comm_2D,1,1,rank_low,rank_high)
.....
For the process 2, rank_low=3, rank_high=3
```

Communicators




Figure 39 – Call of the MPI_Cart_shift() subroutine

```
call MPI_CART_SHIFT(comm_3D,0,1,rank_left,rank_right)
.....
For the process 0, rank_left=-1, rank_right=4
```

```
call MPI_CART_SHIFT(comm_3D,1,1,rank_low,rank_high)
.....
For the process 0, rank_low=-1, rank_high=2
```

```
call MPI_CART_SHIFT(comm_3D,2,1,rank_ahead,rank_before)
.....
For the process 0, rank_ahead=-1, rank_before=1
```

Communicators

Example

- create a 2D Cartesian grid periodic in y
- get coordinates of each process
- get neighbours ranks for each process

```
1 program decomposition
2 use mpi
3 implicit none
4
5 integer :: rank_in_topo,nb_procs
6 TYPE(MPI_Comm) :: comm_2D
7 integer, dimension(4) :: neighbor
8 integer, parameter :: N=1,E=2,S=3,W=4
9 integer, parameter :: ndims = 2
10 integer, dimension(ndims) :: dims,coords
11 logical, dimension(ndims) :: periods
12 logical :: reorder
13
14 call MPI_INIT()
15
16 call MPI_COMM_SIZE(MPI_COMM_WORLD,nb_procs)
17
18 ! Know the number of processes along x and y
19 dims(:) = 0
20
21 call MPI_DIMS_CREATE(nb_procs,ndims,dims)
```

Communicators

```
22 ! 2D y-periodic grid creation
23 periods(1) = .false.
24 periods(2) = .true.
25 reorder = .false.
26
27 call MPI_CART_CREATE(MPI_COMM_WORLD,ndims,dims,periods,reorder,comm_2D)
28
29 ! Know my coordinates in the topology
30 call MPI_COMM_RANK(comm_2D,rank_in_topo)
31 call MPI_CART_COORDS(comm_2D,rank_in_topo,ndims,coords)
32
33 ! Search of my West and East neighbors
34 call MPI_CART_SHIFT(comm_2D,0,1,neighbor(W),neighbor(E))
35
36 ! Search of my South and North neighbors
37 call MPI_CART_SHIFT(comm_2D,1,1,voisin(S),voisin(N))
38
39 call MPI_FINALIZE()
40
41 end program decomposition
```

Subdividing a Cartesian topology

- The goal, by example, is to degenerate a 2D or 3D cartesian topology into, respectively, a 1D or 2D Cartesian topology.
- For MPI, degenerating a 2D Cartesian topology creates as many communicators as there are rows or columns in the initial Cartesian grid. For a 3D Cartesian topology, there will be as many communicators as there are planes.
- The major advantage is to be able to carry out collective operations limited to a subgroup of processes belonging to :
 - the same row (or column), if the initial topology is 2D ;
 - the same plane, if the initial topology is 3D.

Communicators




Figure 40 – Two examples of data distribution in a degenerated 2D topology

Communicators

Subdividing a Cartesian topology

There are two ways to degenerate a topology :

- By using the `MPI_Comm_split()` general subroutine
- By using the `MPI_Cart_sub()` subroutine designed for this purpose

```
MPI_CART_SUB(CommCart,remain_dims,CommCartD,code)

logical, intent(in), dimension(NDim) :: remain_dims
TYPE(MPI_Comm), intent(in)           :: CommCart
TYPE(MPI_Comm), intent(out)          :: CommCartD
integer, optional, intent(out)        :: code
```





Figure 41 – Broadcast of a *V* array in the degenerated 2D grid.

Communicators

```
1 program CommCartSub
2 use mpi_f08
3 implicit none
4
5 TYPE(MPI_Comm) :: Comm2D,Comm1D
6 integer :: rank
7 integer,parameter :: NDim2D=2
8 integer,dimension(NDim2D) :: Dim2D,Coord2D
9 logical,dimension(NDim2D) :: Period,remain_dims
10 logical :: Reorder
11 integer,parameter :: m=4
12 real, dimension(m) :: V=0.
13 real :: W=0.
```

Communicators

```
14 call MPI_INIT()
15
16 ! Creation of the initial 2D grid
17 Dim2D(1) = 4
18 Dim2D(2) = 3
19 Period(:) = .false.
20 ReOrder = .false.
21 call MPI_CART_CREATE(MPI_COMM_WORLD,NDim2D,Dim2D,Period,ReOrder,Comm2D)
22 call MPI_COMM_RANK(Comm2D,rank)
23 call MPI_CART_COORDS(Comm2D,rank,NDim2D,Coord2D)
24
25 ! Initialization of the V vector
26 if (Coord2D(1) == 1) V(:)=real(rank)
27
28 ! Every row of the grid must be a 1D cartesian topology
29 remain_dims(1) = .true.
30 remain_dims(2) = .false.
31 ! Subdivision of the 2D cartesian grid
32 call MPI_CART_SUB(Comm2D,remain_dims,Comm1D)
33
34 ! The processes of column 2 distribute the V vector to the processes of their row
35 call MPI_SCATTER(V,1,MPI_REAL,W,1,MPI_REAL,1,Comm1D)
36
37 print'("Rank : ",I2," ; Coordinates : (" ,I1," ,",I1," ) ; W = ",F2.0)', &
38 rank,Coord2D(1),Coord2D(2),W
39
40 call MPI_FINALIZE()
41 end program CommCartSub
```

Communicators

```
> mpiexec -n 12 CommCartSub
```

```
Rank : 0 ; Coordinates : (0,0) ; W = 3.  
Rank : 1 ; Coordinates : (0,1) ; W = 4.  
Rank : 3 ; Coordinates : (1,0) ; W = 3.  
Rank : 8 ; Coordinates : (2,2) ; W = 5.  
Rank : 4 ; Coordinates : (1,1) ; W = 4.  
Rank : 5 ; Coordinates : (1,2) ; W = 5.  
Rank : 6 ; Coordinates : (2,0) ; W = 3.  
Rank : 10 ; Coordinates : (3,1) ; W = 4.  
Rank : 11 ; Coordinates : (3,2) ; W = 5.  
Rank : 9 ; Coordinates : (3,0) ; W = 3.  
Rank : 2 ; Coordinates : (0,2) ; W = 5.  
Rank : 7 ; Coordinates : (2,1) ; W = 4.
```





Figure 42 – Broadcast of a V array in the degenerated 2D grid.

MPI Hands-On – Exercise 6 : Communicators

- Using the Cartesian topology defined below, subdivide in 2 communicators following the lines by calling `MPI_Comm_split()`. Then, have the processes of the second column scatter the V array to the processes of their line.




Figure 43 – Subdivision of a 2D topology and communication using the obtained 1D topology

- Constraint : define the color of each process without using the *modulo* operation.

MPI-IO

Input/Output Optimisation

- Applications which perform large calculations also tend to handle large amounts of data and generate a significant number of I/O requests.
- Effective treatment of I/O can highly improve the global performances of applications.
- I/O tuning of parallel codes involves :
 - Parallelizing I/O access of the program in order to avoid serial bottlenecks and to take advantage of parallel file systems
 - Implementing efficient data access algorithms (nonblocking I/O)
 - Leveraging mechanisms implemented by the operating system (request grouping methods, I/O buffers, etc.).
- Libraries make I/O optimisations of parallel codes easier by providing ready-to-use capabilities.

The MPI-IO interface

- The MPI-2 norm defines a set of functions designed to manage parallel I/O.
- The I/O functions use well-known MPI concepts. For instance, [collectives](#) and [nonblocking operations](#) on files and between MPI processes are similar. Files can also be accessed in a patterned way using the existing [derived datatype](#) functionality.
- Other concepts come from native I/O interfaces (file descriptors, attributes, ...).

Example of a sequential optimisation implemented by I/O libraries

- I/O performance suffers considerably when making many small I/O requests.
- Access on small, non-contiguous regions of data can be optimized by grouping requests and using temporary buffers.
- Such optimisation is performed automatically by MPI-IO libraries.




Figure 44 – Data sieving mechanism improving I/O access on small, non-contiguous data set.

Example of a parallel optimisation

Collective I/O access can be optimised by rebalancing the I/O operations in contiguous chunks and performing inter-process communications.




Figure 45 – Read operation performed in two steps by a group of processes

Open a file

```
MPI_File_open(comm, filename, amode, info, fh, code)

TYPE(MPI_Comm), intent(in)      :: comm
character(len=*), intent(in)    :: filename
integer, intent(in)             :: amode
TYPE(MPI_Info), intent(in)      :: info
TYPE(MPI_File), intent(out)     :: fh
integer, optional, intent(out)   :: code
```

- Open the file `filename` with access modes `amode`;
- `fh` is an opaque representation of the opened file ;
- Opening is a `collective operation` ;
- `filename` and `amode` must be the same for all ranks in the `comm` communicator ;
- `MPI_Info` object are key-value database usefull for optimisation. `MPI_INFO_NULL` could be used as a default value.

Mode

Mode	Meaning
MPI_MODE_RDONLY	Read only
MPI_MODE_RDWR	Reading and writing
MPI_MODE_WRONLY	Write only
MPI_MODE_CREATE	Create the file if it does not exist
MPI_MODE_EXCL	Error if creating file that already exists
MPI_MODE_UNIQUE_OPEN	File will not be concurrently opened elsewhere
MPI_MODE_SEQUENTIAL	File will only be accessed sequentially
MPI_MODE_APPEND	Set initial position of all file pointers to end of file
MPI_MODE_DELETE_ON_CLOSE	Delete file on close

Modes can be combined with IOR function or addition if each term are only used once.

Closing a file

```
MPI_File_close(fh, code)

TYPE(MPI_File), intent(out) :: fh
integer, optional, intent(out) :: code
```

- Close the file ;
- Closing is a *collective* operation.

```
1 program open01
2   use mpi_f08
3   implicit none
4   character(len=MPI_MAX_ERROR_STRING) :: error_text
5   TYPE(MPI_File) :: fh
6   integer :: code, error_len
7
8   call MPI_INIT()
9
10  call MPI_FILE_OPEN(MPI_COMM_WORLD, "file.data", &
11      MPI_MODE_RDWR + MPI_MODE_CREATE, MPI_INFO_NULL, fh, code)
12  IF (code /= MPI_SUCCESS) THEN
13    CALL MPI_ERROR_STRING(code,error_text,error_len)
14    PRINT *, error_text(1:error_len)
15    CALL MPI_ABORT(MPI_COMM_WORLD, 42)
16  END IF
17
18  call MPI_FILE_CLOSE(fh,code)
19  IF (code /= MPI_SUCCESS) THEN
20    PRINT *, 'Error in closing file'
21    CALL MPI_ABORT(MPI_COMM_WORLD, 2)
22  END IF
23  call MPI_FINALIZE()
24
25 end program open01
```

```
> ls -l file.data
-rw----- 1 user      grp  0 Feb 08 12:13 file.data
```

Error handling

- The behavior concerning code argument is different for the IO part of MPI.
- It's necessary to check the value of this argument.
- It's possible to change this behaviour with `MPI_File_set_errhandler()`.
- Two error handlers are available : `MPI_ERRORS_ARE_FATAL` and `MPI_ERRORS_RETURN`.
- `MPI_Comm_set_errhandler()` provides a way to change the error handler for the communications.

```
MPI_FILE_SET_ERRHANDLER(fh,errhandler,code)

TYPE(MPI_File), intent(inout)    :: fh
TYPE(MPI_Errhandler), intent(in) :: errhandler
integer, optional, intent(out)   :: code
```

The default behaviour can be changed with `MPI_FILE_NULL` as file handler.

Data access routines

- MPI-IO proposes a broad range of subroutines for transferring data between files and memory.
- Subroutines can be distinguished through several properties :
 - The **position** in the file can be specified using an **explicit offset** (ie. an absolute position relative to the beginning of the file) or using **individual** or **shared** file pointers (ie. the offset is defined by the current value of pointers).
 - Data access can be **blocking** or **nonblocking**.
 - Sending and receiving messages can be **collective** (in the communicator group) or **noncollective**.
- Different access methods may be mixed within the same program.

Positioning	Synchronization	noncollective	collective
explicit offsets	blocking	<code>MPI_File_read_at</code> <code>MPI_File_write_at</code>	<code>MPI_File_read_at_all</code> <code>MPI_File_write_at_all</code>
	nonblocking	<code>MPI_File_iread_at</code> <code>MPI_File_iwrite_at</code>	<code>MPI_File_iread_at_all</code> <code>MPI_File_iwrite_at_all</code>
individual file pointers	blocking	<code>MPI_File_read</code> <code>MPI_File_write</code>	<code>MPI_File_read_all</code> <code>MPI_File_write_all</code>
	nonblocking	<code>MPI_File_iread</code> <code>MPI_File_iwrite</code>	<code>MPI_File_iread_all</code> <code>MPI_File_iwrite_all</code>
shared file pointer	blocking	<code>MPI_File_read_shared</code> <code>MPI_File_write_shared</code>	<code>MPI_File_read_ordered</code> <code>MPI_File_write_ordered</code>
	nonblocking	<code>MPI_File_iread_shared</code> <code>MPI_File_iwrite_shared</code>	<code>MPI_File_read_ordered_begin</code> <code>MPI_File_read_ordered_end</code> <code>MPI_File_write_ordered_begin</code> <code>MPI_File_write_ordered_end</code>

File Views

- By default, files are treated as a sequence of bytes but access patterns can also be expressed using predefined or derived MPI datatypes.
- This mechanism is called [file views](#) and is described in further detail later.
- For now, we only need to know that the [views](#) rely on an [elementary data type](#) and that the default type is [MPI_BYTE](#).

Explicit Offsets

```
MPI_File_read_at(fh, offset, buf, count, datatype, iostatus, code)
MPI_File_write_at(fh, offset, buf, count, datatype, iostatus, code)

TYPE(MPI_File), INTENT(IN)          :: fh
INTEGER(KIND=MPI_OFFSET_KIND), INTENT(IN) :: offset
TYPE(*), DIMENSION(..)             :: buf
INTEGER, INTENT(IN)                :: count
TYPE(MPI_Datatype), INTENT(IN)     :: datatype
TYPE(MPI_Status)                  :: iostatus
INTEGER, OPTIONAL, INTENT(OUT)     :: code
```

- Write/read at offset `offset` in the file `fh`, `count` element of type `datatype` from address `buf`;
- The `offset` is expressed as a multiple of the `elementary data type` of the current view (therefore, the default offset unit is bytes).
- The `datatype` size must be a multiple of the elementary datatype.

```
1 program write_at
2 use mpi_f08
3 implicit none
4 integer, parameter :: nb_values=10
5 integer :: i,rank,code,bytes_in_integer
6 TYPE(MPI_File) :: fh
7 integer(kind=MPI_OFFSET_KIND) :: offset
8 integer, dimension(nb_values) :: values
9 TYPE(MPI_Status) :: iostatus
10
11 call MPI_INIT()
12 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13 values(:)= (/ (i+rank*100,i=1,nb_values) /)
14 print *, "process",rank, ":" ,values(:)
15
16 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_WRONLY + MPI_MODE_CREATE, &
17 MPI_INFO_NULL,fh,code)
18 IF (code /= MPI_SUCCESS) THEN
19 PRINT *, 'Error in opening file'
20 CALL MPI_ABORT(MPI_COMM_WORLD, 42)
21 END IF
22 call MPI_TYPE_SIZE(MPI_INTEGER,bytes_in_integer)
23 offset=rank*nb_values*bytes_in_integer
24
25 call MPI_FILE_SET_ERRHANDLER(fh,MPI_ERRORS_ARE_FATAL)
26 call MPI_FILE_WRITE_AT(fh,offset,values,nb_values,MPI_INTEGER, &
27 iostatus)
28
29 call MPI_FILE_CLOSE(fh)
30 call MPI_FINALIZE()
31 end program write_at
```




Figure 46 – MPI_File_write_at()

```
> mpiexec -n 2 write_at
process 0 :    1,    2,    3,    4,    5,    6,    7,    8,    9,    10
process 1 :  101,  102,  103,  104,  105,  106,  107,  108,  109,  110
```

```
1 program read_at
2
3 use mpi_f08
4 implicit none
5
6 integer, parameter :: nb_values=10
7 integer :: rank,code,bytes_in_integer
8 TYPE(MPI_File) :: fh
9 integer(kind=MPI_OFFSET_KIND) :: offset
10 integer, dimension(nb_values) :: values
11 TYPE(MPI_Status) :: iostatus
12
13 call MPI_INIT()
14 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
15 call MPI_FILE_SET_ERRHANDLER(MPI_FILE_NULL,MPI_ERRORS_ARE_FATAL);
16 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
17     fh,code)
18
19 call MPI_TYPE_SIZE(MPI_INTEGER,bytes_in_integer)
20
21 offset=rank*nb_values*bytes_in_integer
22 call MPI_FILE_READ_AT(fh,offset,values,nb_values,MPI_INTEGER, &
23     iostatus)
24 print *, "process",rank,":",values(:)
25
26 call MPI_FILE_CLOSE(fh)
27 call MPI_FINALIZE()
28
29 end program read_at
```




Figure 47 – MPI_File_read_at ()

```
> mpiexec -n 2 read_at
process 0 :  1,   2,   3,   4,   5,   6,   7,   8,   9,   10
process 1 : 101, 102, 103, 104, 105, 106, 107, 108, 109, 110
```

Individual file pointers

```
MPI_File_read(descripteur, buf, count, datatype, statut, code)
MPI_File_write(descripteur, buf, count, datatype, statut, code)

TYPE(MPI_File), INTENT(IN)           :: descripteur
TYPE(*), DIMENSION(..)              :: buf
INTEGER, INTENT(IN)                 :: count
TYPE(MPI_Datatype), INTENT(IN)      :: datatype
TYPE(MPI_Status)                    :: statut
INTEGER, OPTIONAL, INTENT(OUT)       :: code
```

- Write/read in the file `fh`, `count` element of type `datatype` from address `buf`;
- MPI maintains `one` individual file pointer per process per `file handle`.
- After an individual file pointer operation is initiated, the individual file pointer is updated to point to the next data item.
- The shared file pointer is neither used nor updated.

```
1 program read01
2
3 use mpi_f08
4 implicit none
5
6 integer, parameter :: nb_values=10
7 integer :: rank,code
8 TYPE(MPI_File) :: fh
9 integer, dimension(nb_values) :: values
10 TYPE(MPI_Status) :: iostatus
11
12 call MPI_INIT()
13 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
14
15 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
16     fh,code)
17
18 call MPI_FILE_READ(fh,values,6,MPI_INTEGER,iostatus)
19 call MPI_FILE_READ(fh,values(7),4,MPI_INTEGER,iostatus)
20
21 print *, "process",rank,":",values(:)
22
23 call MPI_FILE_CLOSE(fh)
24 call MPI_FINALIZE()
25
26 end program read01
```




Figure 48 – Example 1 of MPI_File_read()

```
> mpiexec -n 2 read01

process 1 :  1,  2,  3,  4,  5,  6,  7,  8,  9,  10
process 0 :  1,  2,  3,  4,  5,  6,  7,  8,  9,  10
```

```
1 program read02
2 use mpi
3 implicit none
4
5 integer, parameter :: nb_values=10
6 integer :: rank,code
7 TYPE(MPI_File) :: fh
8 integer, dimension(nb_values) :: values=0
9 TYPE(MPI_Status) :: iostatus
10
11 call MPI_INIT()
12 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13
14 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
15 fh,code)
16
17 if (rank == 0) then
18   call MPI_FILE_READ(fh,values,5,MPI_INTEGER,iostatus)
19 else
20   call MPI_FILE_READ(fh,values,8,MPI_INTEGER,iostatus)
21   call MPI_FILE_READ(fh,values,5,MPI_INTEGER,iostatus)
22 end if
23
24 print *, "process",rank,":",values(1:8)
25
26 call MPI_FILE_CLOSE(fh)
27 call MPI_FINALIZE()
28 end program read02
```

MPI-IO




Figure 49 – Example 2 of MPI_File_read()

```
> mpiexec -n 2 read02

process 0 :  1,   2,   3,   4,   5,   0,   0,   0
process 1 :  9,  10, 101, 102, 103,   6,   7,   8
```

Shared file pointers

```
MPI_File_read_shared(fh, buf, count, datatype, iostatus, code)
MPI_File_write_shared(fh, buf, count, datatype, iostatus, code)

TYPE(MPI_File), INTENT(IN)          :: descripteur
TYPE(*), DIMENSION(..)             :: buf
INTEGER, INTENT(IN)                :: count
TYPE(MPI_Datatype), INTENT(IN)     :: datatype
TYPE(MPI_Status)                   :: statut
INTEGER, OPTIONAL, INTENT(OUT)      :: code
```

- Write/read in the file `fh`, `count` element of type `datatype` from address `buf`;
- MPI maintains only one shared file pointer per file (shared among processes in the communicator group).
- All processes must use the `same file view`.
- For the noncollective shared file pointer routines, the order `is not deterministic`. To enforce a specific order, the user needs to use other synchronisation means or use collective variants.
- After a shared file pointer operation, the shared file pointer is updated to point to the next data item, that is, just after the last one accessed by the operation.
- The individual file pointers are neither used nor updated.

```
1 program read_shared01
2
3 use mpi_f08
4 implicit none
5
6 integer :: rank,code
7 TYPE(MPI_File) :: fh
8 integer, parameter :: nb_values=10
9 integer, dimension(nb_values) :: values
10 TYPE(MPI_Status) :: iostatus
11
12 call MPI_INIT()
13 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
14
15 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
16           fh,code)
17
18 call MPI_FILE_READ_SHARED(fh,values,4,MPI_INTEGER,iostatus)
19 call MPI_FILE_READ_SHARED(fh,values(5),6,MPI_INTEGER,iostatus)
20
21 print *, "process",rank,":",values(:)
22
23 call MPI_FILE_CLOSE(fh)
24 call MPI_FINALIZE()
25
26 end program read_shared01
```




Figure 50 – Example of MPI_File_read_shared()

```
> mpiexec -n 2 read_shared01
process 1 : 1, 2, 3, 4, 5, 6, 7, 8, 9, 10
process 0 : 101, 102, 103, 104, 105, 106, 107, 108, 109, 110
```

Collective data access

- Collective operations require the participation of all the processes within the **communicator** group associated with the file handle.
- Collective operations may **perform much better** than their noncollective counterparts, as global data accesses have significant potential for automatic optimisation.
- For the collective shared file pointer routines, the accesses to the file will be **in the order** determined by the ranks of the processes within the group. The ordering is therefore **deterministic**.

Interfaces

```
MPI_File_read_at_all(fh, offset, buf, count, datatype, iostatus, code)
MPI_File_write_at_all(fh, offset, buf, count, datatype, iostatus, code)

MPI_File_read_all(fh, buf, count, datatype, iostatus, code)
MPI_File_write_all(fh, buf, count, datatype, iostatus, code)

MPI_File_read_ordered(fh, buf, count, datatype, iostatus, code)
MPI_File_write_ordered(fh, buf, count, datatype, iostatus, code)

TYPE(MPI_File), INTENT(IN) :: fh
INTEGER(KIND=MPI_OFFSET_KIND), INTENT(IN) :: offset
TYPE(*), DIMENSION(..) :: buf
INTEGER, INTENT(IN) :: count
TYPE(MPI_Datatype), INTENT(IN) :: datatype
TYPE(MPI_Status) :: iostatus
INTEGER, OPTIONAL, INTENT(OUT) :: code
```

```
1 program read_at_all
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_values=10
6 integer :: rank,code,bytes_in_integer
7 TYPE(MPI_File)
8 integer(kind=MPI_OFFSET_KIND) :: offset_file
9 integer, dimension(nb_values) :: values
10 TYPE(MPI_Status) :: iostatus
11
12 call MPI_INIT()
13 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
14
15 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
16     fh)
17
18 call MPI_TYPE_SIZE(MPI_INTEGER,bytes_in_integer)
19 offset_file=rank*nb_values*bytes_in_integer
20 call MPI_FILE_READ_AT_ALL(fh,offset_file,values,nb_values, &
21     MPI_INTEGER,iostatus)
22 print *, "process",rank,":",values(:)
23
24 call MPI_FILE_CLOSE(fh)
25 call MPI_FINALIZE()
26 end program read_at_all
```




Figure 51 – Example of MPI_File_read_at_all()

```
> mpiexec -n 2 read_at_all
process 0 :  1,   2,   3,   4,   5,   6,   7,   8,   9,   10
process 1 : 101, 102, 103, 104, 105, 106, 107, 108, 109, 110
```

```
1 program read_all01
2 use mpi_f08
3 implicit none
4
5 integer :: rank,code
6 TYPE(MPI_File) :: fh
7 integer, parameter :: nb_values=10
8 integer, dimension(nb_values) :: values
9 TYPE(MPI_Status) :: iostatus
10
11 call MPI_INIT()
12 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13
14 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
15     fh)
16
17 call MPI_FILE_READ_ALL(fh,values,4,MPI_INTEGER,iostatus)
18 call MPI_FILE_READ_ALL(fh,values(5),6,MPI_INTEGER,iostatus)
19
20 print *, "process ",rank, ":",values(:)
21
22 call MPI_FILE_CLOSE(fh)
23 call MPI_FINALIZE()
24 end program read_all01
```




Figure 52 – Example 1 of MPI_File_read_all()

```
> mpiexec -n 2 read_all01  
process 0 : 1, 2, 3, 4, 5, 6, 7, 8, 9, 10  
process 1 : 1, 2, 3, 4, 5, 6, 7, 8, 9, 10
```

```
1 program read_all02
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_values=10
6 integer :: rank, index1, index2, code
7 type(MPI_File)
8 integer, dimension(nb_values) :: values=0
9 type(MPI_Status) :: iostatus
10
11 call MPI_INIT()
12 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
14          fh)
15
16 if (rank == 0) then
17     index1=3
18     index2=6
19 else
20     index1=5
21     index2=9
22 end if
23
24 call MPI_FILE_READ_ALL(fh,values(index1),index2-index1+1, &
25                      MPI_INTEGER,iostatus)
26 print *, "process",rank,":",values(:)
27
28 call MPI_FILE_CLOSE(fh)
29 call MPI_FINALIZE()
30 end program read_all02
```




Figure 53 – Example 2 of MPI_File_read_all()

```
> mpiexec -n 2 read_all02
process 1 : 0, 0, 0, 0, 1, 2, 3, 4, 5, 0
process 0 : 0, 0, 1, 2, 3, 4, 0, 0, 0
```

```
1 program read_all03
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_values=10
6 integer :: rank,code
7 type(MPI_File) :: fh
8 integer, dimension(nb_values) :: values=0
9 type(MPI_Status) :: iostatus
10
11 call MPI_INIT()
12 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13
14 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
15     fh)
16
17 if (rank == 0) then
18     call MPI_FILE_READ_ALL(fh,values(3),4,MPI_INTEGER,iostatus)
19 else
20     call MPI_FILE_READ_ALL(fh,values(5),5,MPI_INTEGER,iostatus)
21 end if
22
23 print *, "process",rank,":",values(:)
24
25 call MPI_FILE_CLOSE(fh)
26 call MPI_FINALIZE()
27 end program read_all03
```




Figure 54 – Example 3 of MPI_File_read_all()

```
> mpiexec -n 2 read_all03
process 1 : 0, 0, 0, 0, 1, 2, 3, 4, 5, 0
process 0 : 0, 0, 1, 2, 3, 4, 0, 0, 0
```

```
1 program read_ordered
2 use mpi_f08
3 implicit none
4
5 integer :: rank,code
6 TYPE(MPI_File) :: fh
7 integer, parameter :: nb_values=10
8 integer, dimension(nb_values) :: values
9 TYPE(MPI_Status) :: iostatus
10
11 call MPI_INIT()
12 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13
14 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
15     fh)
16
17 call MPI_FILE_READ_ORDERED(fh,values,4,MPI_INTEGER,iostatus)
18 call MPI_FILE_READ_ORDERED(fh,values(5),6,MPI_INTEGER,iostatus)
19
20 print *, "process",rank,":",values(:)
21
22 call MPI_FILE_CLOSE(fh)
23 call MPI_FINALIZE()
24 end program read_ordered
```




Figure 55 – Example of MPI_File_ordered()

```
> mpiexec -n 2 read_ordered

process 1 : 5, 6, 7, 8, 105, 106, 107, 108, 109, 110
process 0 : 1, 2, 3, 4, 9, 10, 101, 102, 103, 104
```

Positioning the file pointers

```
MPI_File_seek(fh, offset, whence, code)
MPI_File_seek_shared(fh, offset, whence, code)

TYPE(MPI_File), INTENT(IN)          :: fh
INTEGER(KIND=MPI_OFFSET_KIND), INTENT(IN) :: offset
INTEGER, INTENT(IN)                 :: whence
INTEGER, OPTIONAL, INTENT(OUT)       :: code
```

- `MPI_File_seek()` and `MPI_File_seek_shared()` updates the file pointer values by using the following possible modes :
 - `MPI_SEEK_SET` : The pointer is set to offset.
 - `MPI_SEEK_CUR` : The pointer is set to the current pointer position plus offset.
 - `MPI_SEEK_END` : The pointer is set to the end of file plus offset.
- With `MPI_SEEK_CUR` and `MPI_SEEK_END`, the `offset` can be negative, which allows seeking backwards.

```
1 program seek
2 use mpi_f08
3 implicit none
4 integer, parameter :: nb_values=10
5 integer :: rank,bytes_in_integer,code
6 TYPE(MPI_File)
7 integer(kind=MPI_OFFSET_KIND) :: fh
8 integer, dimension(nb_values) :: values
9 TYPE(MPI_Status) :: iostatus
10
11 call MPI_INIT()
12 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
14 fh)
15
16 call MPI_FILE_READ(fh,values,3,MPI_INTEGER,iostatus)
17 call MPI_TYPE_SIZE(MPI_INTEGER,bytes_in_integer)
18 offset=8*bytes_in_integer
19 call MPI_FILE_SEEK(fh,offset,MPI_SEEK_CUR)
20 call MPI_FILE_READ(fh,values(4),3,MPI_INTEGER,iostatus)
21 offset=4*bytes_in_integer
22 call MPI_FILE_SEEK(fh,offset,MPI_SEEK_SET)
23 call MPI_FILE_READ(fh,values(7),4,MPI_INTEGER,iostatus)
24
25 print *, "process",rank,":",values(:)
26
27 call MPI_FILE_CLOSE(fh)
28 call MPI_FINALIZE()
29 end program seek
```




Figure 56 – Example of MPI_File_seek()

```
> mpiexec -n 2 seek

process 1 : 1, 2, 3, 102, 103, 104, 5, 6, 7, 8
process 0 : 1, 2, 3, 102, 103, 104, 5, 6, 7, 8
```

Access to end of file

- Writing to the end of the file increases the file size.
- Reading at the end of the file does not retrieve any data. When reading, using `MPI_Get_count()` allows you to know the number of elements actually read.

Nonblocking Data Access

- Nonblocking operations enable overlapping of I/O operations and computations.
- The semantic of nonblocking I/O calls is similar to the semantic of nonblocking communications between processes.
- A first nonblocking I/O call initiates the I/O operation and a separate request call is needed to complete the I/O requests (`MPI_Test()`, `MPI_Wait()`, etc.).

```
1 program iread_at
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_values=10
6 integer :: i,nb_iterations=0,rank,bytes_in_integer,code
7 TYPE(MPI_Request) :: request
8 TYPE(MPI_File) :: fh
9 integer(kind=MPI_OFFSET_KIND) :: offset
10 integer, dimension(nb_values) :: values
11 TYPE(MPI_Status) :: iostatus
12 logical :: finished
13
14 call MPI_INIT()
15 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
```

```
16      call MPI_FILE_OPEN(MPI_COMM_WORLD, "data.dat", MPI_MODE_RDONLY, MPI_INFO_NULL, &
17                      fh)
18
19      call MPI_TYPE_SIZE(MPI_INTEGER, bytes_in_integer)
20
21      offset=rank*nb_values*bytes_in_integer
22      call MPI_FILE_IREAD_AT(fh,offset,values,nb_values, &
23                               MPI_INTEGER,request)
24
25      do while (nb_iterations < 5000)
26          nb_iterations=nb_iterations+1
27          ! Overlapping the I/O operation with computations
28          ...
29          call MPI_TEST(request,finished,iostatus)
30          if (finished) exit
31      end do
32      if (.not. finished) call MPI_WAIT(request,iostatus)
33      print *, "After",nb_iterations,"iterations, process",rank,":",values
34
35      call MPI_FILE_CLOSE(fh)
36      call MPI_FINALIZE()
37
38  end program iread_at
```




Figure 57 – Example of MPI_File_iread_at()

```
> mpiexec -n 2 iread_at
```

```
After 1 iterations, process 0 : 1, 2, 3, 4, 5, 6, 7, 8, 9, 10
```

```
After 1 iterations, process 1 : 101, 102, 103, 104, 105, 106, 107, 108, 109, 110
```

```
1 program iwrite
2 use mpi_f08
3 implicit none
4
5 integer, parameter :: nb_values=10
6 TYPE(MPI_File) :: fh
7 TYPE(MPI_Request) :: request
8 integer :: code, nb_it=0
9 integer(kind=MPI_OFFSET_KIND) :: offset
10 integer, dimension(nb_values) :: values,temp
11 logical :: finished
12
13 call MPI_INIT()
14 !...
15 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_WRONLY+MPI_MODE_CREATE, &
16 MPI_INFO_NULL, fh)
17 temp = values
18 call MPI_FILE_SEEK(fh,offset,MPI_SEEK_SET)
19 call MPI_FILE_IWRITE(fh,temp,nb_values,MPI_INTEGER,request)
20 do while (nb_it < 5000)
21 nb_it = nb_it+1
22 ...
23 call MPI_TEST(request,finished,MPI_STATUS_IGNORE)
24 if (finished) then
25   temp = values
26   call MPI_FILE_SEEK(fh,offset,MPI_SEEK_SET)
27   call MPI_FILE_IWRITE(fh,temp,nb_values,MPI_INTEGER,request)
28 end if
29 end do
30 call MPI_WAIT(request,MPI_STATUS_IGNORE)
31 call MPI_FILE_CLOSE(fh)
32 call MPI_FINALIZE()
33 end program iwrite
```

Nonblocking and collective data access routines

- It is possible to perform operations that are both **collective** and **nonblocking**.
- Only one collective nonblocking operation can be in progress on any MPI process at a time.
- Between the two parts of the collective nonblocking operation, individual operations on the file are allowed, but the memory region involved in the collective operation cannot be modified.

```
1 program iread_all
2
3 use mpi_f08
4 implicit none
5
6 integer :: rank,code
7 TYPE(MPI_File) :: fh
8 integer, parameter :: nb_values=10
9 integer, dimension(nb_values) :: values
10 TYPE(MPI_Status) :: iostatus
11 TYPE(MPI_Request) :: req
12
13 call MPI_INIT()
14 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
15
16 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
17           fh)
18
19 call MPI_FILE_IREAD_ALL(fh,values,4,MPI_INTEGER,req)
20 print *, "Process      :",rank
21 call MPI_WAIT(req,iostatus)
22
23 print *, "process",rank,":",values(1:4)
24
25 call MPI_FILE_CLOSE(fh)
26 call MPI_FINALIZE()
27
28 end program iread_all
```

MPI-IO




Figure 58 – Example of MPI_File_iread_all()

```
> mpiexec -n 2 iread_all

Process      : 0
process 0 : 1, 2, 3, 4
Process      : 1
process 1 : 1, 2, 3, 4
```

MPI Hands-On – Exercise 7 : Read an MPI-IO file

- We have a binary file `data.dat` with 484 integer values.
- With 4 processes, it consists of reading the 121 first values on process 0, the 121 next on the process 1, and so on.
- We will use 4 different methods :
 - Read via explicit offsets, in individual mode
 - Read via shared file pointers, in collective mode
 - Read via individual file pointers, in individual mode
 - Read via shared file pointers, in individual mode
- To compile use `make`, to execute use `make exe`, and to verify the results use `make verification` which build figure file corresponding to the four cases.

MPI 4.x

Interopérabilité

For example, for `MPI_RECV()` the interface with the `mpi` module is :

```
<type> buf(*)
INTEGER :: count, datatype, source, tag, comm, ierror
INTEGER, DIMENSION(MPI_STATUS_SIZE) :: statut
```

With the `mpi_f08` module :

```
TYPE(*), DIMENSION(..) :: buf
INTEGER :: count, source, tag
TYPE(MPI_DATATYPE) :: datatype
TYPE(MPI_COMM) :: comm
TYPE(MPI_STATUS) :: statut
INTEGER, optional :: ierror
```

These new types are in fact INTEGER

```
TYPE, BIND(C) :: MPI_COMM
  INTEGER :: MPI_VAL
END TYPE MPI_COMM
```

With the `mpi_f08` module, expression `comm%mpi_val` is equivalent to argument `comm` in `mpi` module.

Adding

- Large count
- Partitioned communication
- MPI Session
- Others

Large count

- Count parameters were in `integer` or `int`.
- MPI 4.0 add new functions with `MPI_Count` instead.
- In C these new functions have `_c` at the end.

```
int MPI_Send(const void * buf, int count, MPI_Datatype datatype, int dest, int tag, MPI_Comm comm);
int MPI_Send_c(const void * buf, MPI_Count count, MPI_Datatype datatype, int dest, int tag, MPI_Comm comm);
```

- In Fortran count in `integer` can be changed in `integer(kind=MPI_COUNT_KIND)`
- Only available with the `mpi_f08` module
- No change in the name of function with polymorphism

```
MPI_Send(buf,count,datatype,dest,tag,comm,ierror)
TYPE(*), DIMENSION(..), INTENT(IN) :: buf
INTEGER, INTENT(IN) :: count, dest, tag
TYPE(MPI_Datatype), INTENT(IN) :: datatype
TYPE(MPI_Comm), INTENT(IN) :: comm
INTEGER, OPTIONAL, INTENT(OUT) :: ierror

MPI_Send(buf,count,datatype,dest,tag,comm,ierror)
TYPE(*), DIMENSION(..), INTENT(IN) :: buf
INTEGER(KIND=MPI_COUNT_KIND), INTENT(IN) :: count
TYPE(MPI_Datatype), INTENT(IN) :: datatype
INTEGER, INTENT(IN) :: dest, tag
TYPE(MPI_Comm), INTENT(IN) :: comm
INTEGER, OPTIONAL, INTENT(OUT) :: ierror
```

Partitioned communication

- Multiple contribution to a communication.
- Useful in hybrid.
- Init with `MPI_Psend_init()` or `MPI_Precv_init()` by providing the count by partition and the number of partition.
- `MPI_Start()` to start the communication.
- `MPI_Pready()` to indicate that a partition is ready.
- Could not mix `MPI_Recv()` and `MPI_Psend_init()`.
- `MPI_Wait()` to wait for the end of communication.
- `MPI_Parrived()` to know if a partition has been received.

Session

- A way to do multiple `MPI_Init()`/`MPI_Finalize()`.
- `MPI_Session_init()` to start a session.
- `MPI_Session_finalize()` to end a session.
- No more `MPI_COMM_WORLD`.
- *Process Sets* : `mpi://WORLD` and `mpi://SELF`.
- `MPI_Group_from_session_pset()` to make a group from a *pset*.
- `MPI_Comm_create_from_group()` to make a communicator from a group.
- `MPI_Session_get_num_psets()` to known the number of *pset* available.
- `MPI_Session_get_nth_pset()` to get the name of a *pset*.

Others

- Add of `MPI_Irecv` and `MPI_Irecv_replace`.
- Add persistent collective communication.
- Add option `mpi_initial_errhandler` for `mpiexec` to specify the default errhandler.

MPI-IO Views

The View Mechanism

- File Views is a mechanism which accesses data in a high-level way. A view describes a template for accessing a file.
- The view that a given process has of an open file is defined by three components : the elementary data type, file type and an initial displacement.
- The view is determined by the repetition of the filetype pattern, beginning at the displacement.




Figure 59 – Tiling a file with a filetype

The View Mechanism

- File Views are defined using MPI datatypes.
- Derived datatypes can be used to structure accesses to the file. For example, elements can be skipped during data access.
- The default view is a linear byte stream (displacement is zero, etype and filetype equal to MPI_BYTE).

Multiple Views

- Each process can successively use several views on the same file.
- Each process can define its own view of the file and access complementary parts of it.

MPI-IO Views




Figure 60 – Separate views, each using a different filetype, can be used to access the file

Limitations :

- Shared file pointer routines are not useable except when all the processes have the same file view.
- If the file is opened for writing, the different views may not overlap, even partially.

Changing the process's view of the data in the file : `MPI_File_set_view()`

```
MPI_FILE_SET_VIEW(fh, displacement, etype, filetype,
                   mode, info, code)

TYPE(MPI_File), intent(in)          :: fh
integer(kind=MPI_OFFSET_KIND), intent(in) :: displacement
TYPE(MPI_Datatype), intent(in)        :: etype, filetype
character(len=*), intent(in)         :: mode
TYPE(MPI_Info), intent(in)           :: info
integer, optional, intent(out)       :: code
```

- This operation is **collective** throughout the file handle. The values for the **initial displacement** and the **filetype** may vary between the processes in the group. The extents of **elementary types** must be identical.
- In addition, the individual file pointers and the shared file pointer are **reset to zero**, taking the initial displacement into account.

Notes :

- The datatypes passed in must have been committed using the `MPI_Type_commit()` subroutine.
- MPI defines three data representations (**mode**) : "native", "internal" or "external32".

Subarray datatype constructor

A derived data type useful to create a filetype is the “subarray” type, that we introduce here. This type allows creating a subarray from an array and can be defined with the `MPI_Type_create_subarray()` subroutine.

The `shape` of an array is a vector for which each element equals the number of array elements in each dimension. For example, the array `T(10, 0:5, -10:10)` (or `T[10][6][21]`), its shape is the `(10,6,21)` vector.

MPI-IO Views / Derived Datatypes

```
MPI_TYPE_CREATE_SUBARRAY(nb_dims,shape_array,shape_sub_array,coord_start,  
                      order,old_type,new_type,code)  
  
integer, intent(in)          :: nb_dims  
integer, dimension(nb_dims), intent(in) :: shape_array,shape_sub_array,coord_start  
integer, intent(in)          :: order  
TYPE(MPI_Datatype), intent(in)    :: old_type  
TYPE(MPI_Datatype), intent(out)   :: new_type  
integer, optional, intent(out)   :: code
```

Explanation of the arguments

- **nb_dims** : number of dimension of the array
- **shape_array** : shape of the array from which a subarray will be extracted
- **shape_sub_array** : shape of the subarray
- **coord_start** : start coordinates if the indices of the array start at 0. For example, if we want the start coordinates of the subarray to be `array(2, 3)`, we must have `coord_start(:)=(/ 1, 2 /)`
- **order** : storage order of elements
 - `MPI_ORDER_FORTRAN` for the ordering used by Fortran arrays (column-major order)
 - `MPI_ORDER_C` for the ordering used by C arrays (row-major order)

MPI-IO Views / Derived Datatypes

Exchanges between 2 process with subarray

BEFORE

1	5	9
2	6	10
3	7	11
4	8	12

Processus 0

AFTER

1	5	9
-7	-11	10
-8	-12	11
4	8	12

Processus 0

-1	-5	-9
-2	-6	-10
-3	-7	-11
-4	-8	-12

Processus 1

-1	-5	-9
-2	-6	-10
-3	2	6
-4	3	7

Processus 1

MPI-IO Views / Derived Datatypes

Exchanges between the two processes (Part 1/2)

```
1 program subarray
2
3 use mpi_f08
4 implicit none
5
6 integer,parameter :: nb_lines=4,nb_columns=3,&
7                      tag=1000,nb_dims=2
8 integer :: code,rank,i
9 TYPE(MPI_Datatype) :: type_subarray
10 integer,dimension(nb_lines,nb_columns) :: tab
11 integer,dimension(nb_dims) :: shape_array,shape_subarray,coord_start
12 TYPE(MPI_Status) :: msgstatus
13
14 call MPI_INIT()
15 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
16
17 !Initialization of the tab array on each process
18 tab(:,:) = reshape( (/ (sign(i,-rank),i=1,nb_lines*nb_columns) /) , &
19                      (/ nb_lines,nb_columns /) )
```

MPI-IO Views / Derived Datatypes

Exchanges between the two processes (Part 2/2)

```
20 !Shape of the tab array from which a subarray will be extracted
21 shape_tab(:) = shape(tab)
22 !The F95 shape function gives the shape of the array put in argument.
23 !ATTENTION, if the concerned array was not allocated on all the processes,
24 !it is necessary to explicitly put the shape of the array in order for it
25 !to be known on all the processes, shape_array(:) = (/ nb_lines,nb_columns /)
26
27 !Shape of the subarray
28 shape_subarray(:) = (/ 2,2 /)
29
30 !Start coordinates of the subarray
31 !For the process 0 we start from the tab(2,1) element
32 !For the process 1 we start from the tab(3,2) element
33 coord_start(:) = (/ rank+1,rank /)
34
35 !Creation of the type_subarray derived datatype
36 call MPI_TYPE_CREATE_SUBARRAY(nb_dims,shape_array,shape_subarray,coord_start,&
37                               MPI_ORDER_FORTRAN,MPI_INTEGER,type_subarray)
38 call MPI_TYPE_COMMIT(type_subarray)
39
40 !Exchange of the subarrays
41 call MPI_SENDRECV_REPLACE(tab,1,type_subarray,mod(rank+1,2),tag,&
42                           mod(rank+1,2),tag,MPI_COMM_WORLD,msgstatus)
43 call MPI_TYPE_FREE(type_subarray)
44 call MPI_FINALIZE()
45 end program subarray
```

Example 1 : Reading non-overlapping sequences of data segments in parallel




Figure 61 – Example 1 : Reading non-overlapping sequences of data segments in parallel

```
> mpiexec -n 2 read_view01

process 1 : 3, 4, 7, 8, 101, 102, 105, 106, 109, 110
process 0 : 1, 2, 5, 6, 9, 10, 103, 104, 107, 108
```

MPI-IO Views

Example 1




Figure 62 – Example 1 (continued)

```
1  if (rank == 0) coord=1
2  if (rank == 1) coord=3
3
4  call MPI_TYPE_CREATE_SUBARRAY(1, (/4/), (/2/), (/coord - 1/), &
5                                MPI_ORDER_FORTRAN, MPI_INTEGER, filetype)
6  call MPI_TYPE_COMMIT(filetype)
7
8  init_displacement=0
9
10 call MPI_FILE_SET_VIEW(handle,init_displacement,MPI_INTEGER,filetype, &
11                      "native",MPI_INFO_NULL)
```

MPI-IO Views

Example 1 : code

```
1 program read_view01
2 use mpi_f08
3 implicit none
4 integer, parameter :: nb_values=10
5 integer :: rank,coord,code
6 TYPE(MPI_Datatype)
7 TYPE(MPI_File)
8 integer(kind=MPI_OFFSET_KIND) :: init_displacement
9 integer, dimension(nb_values) :: values
10 TYPE(MPI_Status) :: iostatus
11 call MPI_INIT(code)
12 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
13
14 if (rank == 0) coord=1
15 if (rank == 1) coord=3
16
17 call MPI_TYPE_CREATE_SUBARRAY(1, (/4/), (/2/), (/coord - 1/), &
18                               MPI_ORDER_FORTRAN,MPI_INTEGER,filetype)
19 call MPI_TYPE_COMMIT(filetype)
20
21 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
22                   handle)
23
24 init_displacement=0
25 call MPI_FILE_SET_VIEW(handle,init_displacement,MPI_INTEGER,filetype, &
26                       "native",MPI_INFO_NULL)
27 call MPI_FILE_READ(handle,values,nb_values,MPI_INTEGER,iostatus)
28
29 print *, "process",rank,":",values(:)
30
31 call MPI_FILE_CLOSE(handle)
32 call MPI_FINALIZE()
33 end program read_view01
```

MPI-IO Views

Example 2 : Reading data using successive views (Part 1/2)



Figure 63 – Example 2 : Reading data using successive views


```
1 program read_view02
2
3 use mpi
4 implicit none
5
6 integer, parameter :: nb_values=10
7 integer :: rank,code,bytes_in_integer
8 TYPE(MPI_File) :: handle
9 TYPE(MPI_Datatype) :: filetype_1,filetype_2
10 integer(kind=MPI_OFFSET_KIND) :: init_displacement
11 integer, dimension(nb_values) :: values
12 TYPE(MPI_Status) :: iostatus
13
14 call MPI_INIT()
15 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
```

Example 2 (Part 2/2)

```
16 call MPI_TYPE_CREATE_SUBARRAY(1, (/4/), (/2/), (/0/), &
17                                MPI_ORDER_FORTRAN,MPI_INTEGER,filetype_1)
18 call MPI_TYPE_COMMIT(filetype_1)
19
20 call MPI_TYPE_CREATE_SUBARRAY(1, (/3/), (/1/), (/2/), &
21                                MPI_ORDER_FORTRAN,MPI_INTEGER,filetype_2)
22 call MPI_TYPE_COMMIT(filetype_2)
23
24 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
25                    handle)
26
27 ! Read using the first view
28 init_displacement=0
29 call MPI_FILE_SET_VIEW(handle,init_displacement,MPI_INTEGER,filetype_1, &
30                        "native",MPI_INFO_NULL)
31 call MPI_FILE_READ(handle,values,4,MPI_INTEGER,iostatus)
32 call MPI_FILE_READ(handle,values(5),3,MPI_INTEGER,iostatus)
33
34 ! Read using the second view
35 call MPI_TYPE_SIZE(MPI_INTEGER,nb_octets_entier)
36 init_displacement=2*nb_octets_entier
37 call MPI_FILE_SET_VIEW(handle,init_displacement,MPI_INTEGER,filetype_2, &
38                        "native",MPI_INFO_NULL)
39 call MPI_FILE_READ(handle,values(8),3,MPI_INTEGER,iostatus)
40
41 print *, "process",rank,":",values(:)
42
43 call MPI_FILE_CLOSE(handle)
44 call MPI_FINALIZE()
45 end program read_view02
```

MPI-IO Views

Example 2 : Illustration



```
> mpexec -n 2 read_view02
```

```
process 1 : 1, 2, 5, 6, 9, 10, 103, 5, 8, 101
process 0 : 1, 2, 5, 6, 9, 10, 103, 5, 8, 101
```

MPI-IO Views

Example 3 : Dealing with holes in datatypes (Part 1/2)




Figure 64 – Example 3 : Dealing with holes in datatypes


```
1 program read_view03_indexed
2 use mpi
3 implicit none
4 integer, parameter :: nb_values=9
5 integer :: rank,bytes_in_integer,code
6 TYPE(MPI_File) :: handle
7 TYPE(MPI_Datatype) :: filetype_tmp,filetype
8 integer(kind=MPI_OFFSET_KIND) :: init_displacement
9 integer(kind=MPI_ADDRESS_KIND) :: lb,extent
10 integer, dimension(2) :: blocklengths,indices
11 integer, dimension(nb_values) :: values
12 TYPE(MPI_Status) :: iostatus
13 call MPI_INIT()
14 call MPI_COMM_RANK(MPI_COMM_WORLD,rank)
```

Example 3 (Part 2/2)

```
15 ! filetype_tmp: MPI type with an extent of 4*MPI_INTEGER
16 indices(1)=0
17 blocklengths(1)=2
18 indices(2)=3
19 blocklengths(2)=1
20 call MPI_TYPE_INDEXED(2,blocklengths,indices,MPI_INTEGER,filetype_tmp)
21
22 ! filetype: MPI type with an extent of 5*MPI_INTEGER
23 call MPI_TYPE_SIZE(MPI_INTEGER,bytes_in_integer)
24 call MPI_TYPE_GET_EXTENT(filetype_tmp,lb,extent)
25 extent = extent + bytes_in_integer
26 call MPI_TYPE_CREATE_RESIZED(filetype_tmp,lb,lb+extent,filetype)
27 call MPI_TYPE_COMMIT(filetype)
28
29 call MPI_FILE_OPEN(MPI_COMM_WORLD,"data.dat",MPI_MODE_RDONLY,MPI_INFO_NULL, &
30           handle)
31
32 init_displacement=0
33 call MPI_FILE_SET_VIEW(handle,init_displacement,MPI_INTEGER,filetype, &
34           "native",MPI_INFO_NULL)
35
36 call MPI_FILE_READ(handle,values,9,MPI_INTEGER,iostatus)
37
38 print *, "process",rank,":",values(:)
39
40 call MPI_FILE_CLOSE(handle)
41 call MPI_FINALIZE()
42
43 end program read_view03_indexed
```

MPI-IO Views

Example 3 : Illustration



```
> mpieexec -n 2 read_view03
```

```
process 0 : 1, 2, 4, 6, 7, 9, 101, 102, 104
process 1 : 1, 2, 4, 6, 7, 9, 101, 102, 104
```

Example 3 : Alternative implementation using a structure datatype

```
1 program read_view03_struct
2 [...]
3 integer(kind=MPI_ADDRESS_KIND), dimension(2) :: displacements
4 [...]
5
6 call MPI_TYPE_CREATE_SUBARRAY(1, (/3/), (/2/), (/0/), MPI_ORDER_FORTRAN, &
7     MPI_INTEGER,tmp_filetype1)
8
9 call MPI_TYPE_CREATE_SUBARRAY(1, (/2/), (/1/), (/0/), MPI_ORDER_FORTRAN, &
10    MPI_INTEGER,tmp_filetype2)
11
12 call MPI_TYPE_SIZE(MPI_INTEGER,bytes_in_integer)
13
14 displacements(1) = 0
15 displacements(2) = 3*bytes_in_integer
16
17 call MPI_TYPE_CREATE_STRUCT(2, (/1,1/),displacements,&
18     (/tmp_filetype1,tmp_filetype2/),filetype)
19 call MPI_TYPE_COMMIT(filetype)
20
21 [...]
22
23 end program read_view03_struct
```

Conclusion

MPI-IO offers a high-level interface and a very large set of functionalities. It is possible to carry out complex operations and take advantage of optimizations implemented in the library. MPI-IO also offers good portability

Advice

- The use of explicitly positioned subroutines in files should be reserved for special cases since the implicit use of individual pointers with views provides a higher level interface.
- When the operations involve all the processes (or a subset identifiable by an MPI sub-communicator), it is generally necessary to favor the **collective** form of the operations.
- Exactly as for the processing of messages when these represent an important part of the application, **nonblocking** is a privileged way of optimization to be implemented by programmers, but this should only be implemented **after** ensuring the correctness of behavior of the application in blocking mode.

Conclusion

Conclusion

- Use blocking point-to-point communications before going to nonblocking communications. It will then be necessary to try to overlap computations and communications.
- Use the blocking I/O functions before going to nonblocking I/O. Similarly, it will then be necessary to overlap I/O-computations.
- Write the communications as if the sends were synchronous (`MPI_Ssend()`).
- Avoid the synchronization barriers (`MPI_Barrier()`), especially on the blocking collective functions.
- MPI/OpenMP hybrid programming can bring gains of scalability. However, in order for this approach to function well, it is obviously necessary to have good OpenMP performance inside each MPI process. A hybrid course is given at IDRIS (<https://cours.idris.fr>).

MPI Hands-On – Exercise 8 : Poisson's equation

Resolution of the following Poisson equation :

$$\begin{cases} \frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} = f(x, y) & \text{in } [0, 1] \times [0, 1] \\ u(x, y) = 0. & \text{on the boundaries} \\ f(x, y) = 2. (x^2 - x + y^2 - y) \end{cases}$$

We will solve this equation with a domain decomposition method :

- The equation is discretized on the domain with a finite difference method.
- The obtained system is resolved with a Jacobi solver.
- The global domain is split into sub-domains.

The exact solution is known and is $u_{exact}(x, y) = xy(x - 1)(y - 1)$

MPI Hands-On – Exercise 8 : Poisson's equation

To discretize the equation, we define a grid with a set of points (x_i, y_j)

$$x_i = i h_x \quad \text{for } i = 0, \dots, ntx + 1$$

$$y_j = j h_y \quad \text{for } j = 0, \dots, nty + 1$$

$$h_x = \frac{1}{(ntx + 1)}$$

$$h_y = \frac{1}{(nty + 1)}$$

h_x : x -wise step

h_y : y -wise step

ntx : number of x -wise interior points

nty : number of y -wise interior points

In total, there are $ntx+2$ points in the x direction
and $nty+2$ points in the y direction.

MPI Hands-On – Exercise 8 : Poisson's equation

- Let u_{ij} be the estimated solution at position $x_i = ih_x$ and $y_j = jh_y$.
- The Jacobi solver consist of computing :

$$u_{ij}^{n+1} = c_0(c_1(u_{i+1j}^n + u_{i-1j}^n) + c_2(u_{ij+1}^n + u_{ij-1}^n) - f_{ij})$$

with : $c_0 = \frac{1}{2} \frac{h_x^2 h_y^2}{h_x^2 + h_y^2}$

$$c_1 = \frac{1}{h_x^2}$$

$$c_2 = \frac{1}{h_y^2}$$

MPI Hands-On – Exercise 8 : Poisson's equation

- In parallel, the interface values of subdomains must be exchanged between the neighbours.
- We use ghost cells as receive buffers.

MPI Hands-On – Exercise 8 : Poisson's equation




Figure 65 – Exchange points on the interfaces

MPI Hands-On – Exercise 8 : Poisson's equation




Figure 66 – Numeration of points in different sub-domains

MPI Hands-On – Exercise 8 : Poisson's equation




Figure 67 – Process rank numbering in the sub-domains

MPI Hands-On – Exercise 8 : Poisson's equation




Figure 68 – Writing the global matrix u in a file

You need to :

- Define a view, to see only the owned part of the global matrix u ;
- Define a type, in order to write the local part of matrix u (without ghost points) ;
- Apply the view to the file ;
- Write using only one call.

MPI Hands-On – Exercise 8 : Poisson's equation

- Initialisation of the MPI environment.
- Creation of the 2D Cartesian topology
- Determination of the array indexes for each sub-domain.
- Determination of the 4 neighbour processes for each sub-domain.
- Creation of two derived datatypes, *type_line* and *type_column*.
- Exchange the values on the interfaces with the other sub-domains.
- Computation of the global error. When the global error is lower than a specified value (machine precision for example), we consider that we have reached the exact solution.
- Collecting of the global matrix u (the same one as we obtained in the sequential) in an MPI-IO file `data.dat`.

MPI Hands-On – Exercise 8 : Poisson's equation

- A skeleton of the parallel version is proposed : It consists of a main program (`poisson.f90`) and several subroutines. All the modifications have to be done in the `parallel.f90` file.
- To compile use `make`, to execute use `make exe`. To verify the results, use `make verification` which runs a reading program of the `data.dat` file and compares it with the sequential version.